

COUNTY CHAVES FIELD Tobac-Pennsylvanian STATE N.M.

OPR HUMBLE OIL & REFG. CO.

MAP

2 New Mexico State "BX"

Sec. 16, T-8-S, R-33-E

CO-ORD

1837' fr S Line & 1997' fr W Line of Sec.

Spud 1-16-65

Comp 2-17-65

CLASS

EL 4397'

CSG & SX - TUBING			LOG:	FORMATION	DATUM	FORMATION	DATUM
10 3/4"	394'		375	Anhy 1802			
7 5/8"	3606'		500	Yates 2350			
4 1/2"	9064'		300	7-R 2452			
				Queen 3019			
				SA 3524			
				Glor 4930			
				Tubb 6408			
				TD 9064'			
				PBD 9041'			

IP Bough "C" Perfs 8980-88' Flwd 336 BOPD. Pot. Based on 15 hr test of 210 BO thru 1/4" chk., TP 300#, gravity 48.3, GOR 1146.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.

PROP DEPTH 9100'

TYPE

DATE

F. R. 1-21-65. Oper's Elev. 4397' DF.
PD 9100' - Bough "C".
Contractor - Cactus Drlg. Co.
1-18-65 Drlg. 1323'.
1-25-65 Drlg. 4925'.
2-1-65 Drlg. 7692'.
2-8-65 Drlg. 8800'.
2-15-65 TD 9064', PB 9041', prep to perf.
LOG TOPS: Abo 7287', W.C. 8112',
Bough "C" 8967'.
2-22-65 TD 9064', PBD 9041', COMPLETED.
Perf @ 8980', 8982', 8984', 8986', 8988' W/1
SPI
Ac. 250 gals.

COUNTY	CHAVES	FIELD	Chaverco	STATE	NM	OWWO
OPR	HUMBLE OIL & REFC. CO.			MAP		
2 State "EX"						
Sec. 16, T-8-S, R-33-E						
1837' FSL, 1997' FWL of Sec.						
Re-Spd 4-26-66						
Re-Cmp 5-2-66						
		FORMATION		DATUM		CLASS
		FORMATION		DATUM		
CSG & SX - TUBING						
10 3/4"		395'		375		
7 5/8"		3606'		500		
4 1/2"		9064'		300		
LOGS EL GR RA IND HC A						
TD 9064', PBD 4426'						

IP San Andres Perfs 4241-4295' Swbd 106 ECPD + 22 BW. Pot.
Based on 12 hr test of 53 EO + 11 BW, gravity 22.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4400'	TYPE	WO
DATE				

F.R. 4-28-66
PD 4400' - SA
(Orig. comp 2-17-65 from Sough "C" perfs
8980-88'; depleted producer 1-6-66, CIE
9064')
Elev. 4397' DF, Orig.
5-16-66 TD 9064', PED 4426', COMPLETE.
Set BP @ 4426'
Perf @ 4241', 4243', 4245', 4247', 4249',
4251', 4253', 4255', 4257', 4259', 4261',
4263', 4265', 4267', 4269', 4271', 4273',
4275', 4277', 4279', 4281', 4283', 4285',
4287', 4289', 4291', 4293', 4295' W/i SPI
Ac (4241-4295') 5000 gals.