

HUMBLE OIL & REFINING COMPANY

New Mexico State BX Well No. 2

HOODS OFFICE O. C. C. 2
PAGE 2
Nov 30 1 53 PM '65

November 30, 1965

WOC. Ran drill pipe and bit. Tagged cement plug at 3650. Pulled drill pipe and bit. Went back in hole open ended with drill pipe and spotted 30 sxs regular neat cement with 2% Cal. Chlo. Pulled drill pipe. WOC. Tagged plug at 3645. Went in hole with drill pipe open ended and spotted 100 sxs of regular neat cement with 2% Cal. Chlo. Pulled drill pipe. WOC. Tagged plug at 3572. Went in hole with bit and drill pipe. Drilled through cement and on down beside fish to 3651 and hit iron. Pulled bit and drill pipe. Went back in hole with mill tool and drill pipe. Milled down to 4375. Pulled drill pipe. Lost mill tool in hole. Went in hole with short catch overshot to 4375. Failed to catch mill tool. Went back in hole with impression block to 3763. Set down couldn't get down. Pulled out of hole. Went in hole with mill tool. Milled down to 4344. Milled beside fish to 4349. Pulled mill tool. Ran impression block. Pulled out of hole. Milled down to 4358. Pulled mill tool. Went back in with mill tool. Milled down to 4909. Circulated clean. Pulled mill tool. Went back in hole and tagged bottom at 4888. Cleaned out 21' of fill and milled to 4913. Circulated clean. Drilled to 4918. Pulled drill pipe. Shut-in well. Well temporary abandoned.