

COUNTY	CHAVES	FIELD	Undesignated	STATE	NM
OPR	SHELL OIL COMPANY				MAP
	1 James-Federal				
	Sec. 24, T-8-S, R-32-E				CO-ORD
	660' fr S & E Lines of Sec.				
	Spud 2-21-65				
	Comp 4-1-65				
		CLASS		EL	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:	Yates 2334			
11 3/4" 319' 350		SA 3537			
8 5/8" 3580' 300		Glor 4932			
5 1/2" 9066' 300		Tubb 6424			
		Abo 7278			
		Wolfe 8405			
LOGS EL GR RA IND HC A		Bo "C" 8969			
		TD 9066', PBD 9022'			

IP Bough "C" Perfs 8970-89' Pmpd 100 BOPD + 154 BW. Pot. Based on 24 hr test, gravity 48.3, GOR 198.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Moran Drlg. Co.	PROP DEPTH 9050'	TYPE
DATE		

F.R. 2-25-65; Oper's Elev. 4428' Df.
PD 9050' - Bough "C"
Contractor - Moran Drlg. Co.
2-23-65 Drlg. 1950'.
3-1-65 Drlg. 4710'.
3-8-65 Drlg. 7287' 1m.
3-15-65 Drlg. 8446'.
3-22-65 TD 9066' 1m., MO Rotary.
3-29-65 TD 9066' 1m., PBD 9023', prep to squeeze.
Perf @ 8971', 8972', 8974', 8975' W/1 SPI
Perf 8981-89' W/2 SPF
Ac. 500 gals.
Flwd 238 BO + 10 BAW in 12 hrs.
Swbd & Flwd 113 BO + 224 BW in 17 hrs.
Ran Tracer.
4-5-65 TD 9066', PBD 9022', tstg on pump.
Re-Perf @ 8972' W/2 shots

4-5-65 - cont. -

Attempted to squeeze perf @ 8972',
Would not break.

Perf @ 8970' W/2 shots

Attempted to squeeze perf @ 8970',
would not break.

CO to 9022'

Pmpd 134 BW in 13½ hrs.

4-12-65 TD 9066', PBD 9022', COMPLETED.