

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N. M. OIL CONW. 80-100000
P. O. BOX 1900
HOBBS, NEW MEXICO

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.
105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2108' FNL & 734' FEL of Section 24-T8S-R32E (Unit H, SENE)

5. Lease Designation and Serial No.

NM-82906

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Shell James A00 Federal #1

9. API Well No.

30-005-10120

10. Field and Pool, or Exploratory Area

Und. Chaveroo San Andres

11. County or Parish, State

Chaves Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Re-entry operations
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-8-94 - Set anchors and re-entry equipment. Moved in and rigged up pulling unit. Nippled up 8-5/8" Larkin head and 10" BOP. Tested BOP and head to 500 psi. Picked up 7-7/8" bit and 4-3/4" drill collars with swivel. Drilled surface plug and fell out of plug at 24'. TIH and tag shoe plug at 3524'. NOTE: Spudded at 2:00 PM 10-7-94. Drilled shoe plug and washed down to 4924'. Circulate and condition mud.

10-9-10-94 - TOOH. Rigged up Schlumberger. Ran open hole logs. TIH w/float shoe, 1 joint of 5-1/2" 15.5# casing, float collar, 29 joints of 5-1/2" sand blasted, 20' marker joint, 81 joints of 5-1/2" 15.5# varnished casing set at 4919'. Cemented with 350 sacks Class C Neat with .5% CF-14. PD 10:00 PM 10-8-94. Bumped plug to 1000#, OK. Set slips. Shut down. 10-12-94 - Cut off 5-1/2" casing. Weld on bell nipple. Installed 5-1/2" Larkin head, adapter and BOP. TIH with 4-3/4" bit, scraper and tubing. Tagged PBSD at 4973'. Displaced hole with 2% KCL. TOOH. Rigged up Schlumberger and ran GR/CBL log. Top of cement at 3750'. TIH with 4" casing guns and perforated 4428-4470' w/8 .42" holes (1 SPF) as follows: 4428, 37, 47, 50, 55, 56, 67 & 4470'. TIH with 5-1/2" Uni V packer and set at 4368'. Acidized perforations 4428-4470' with 1500 gallons 15% NEFE acid and ball sealers. Swabbing.

10-13-94 - Swabbed. Released packer. TOOH. Rigged up Schlumberger and set 5-1/2" cement retainer at 4423'. TIH with stinger on 2-7/8" tubing. Pump through retainer. Pumped 50 sacks Class "C" .4% fluid loss and 50 sacks Class C. Perforations 4428-4470' squeezed to 2000 psi with 90 sacks in formation. Sting out of retainer. Reverse 10 sacks to pit. TOOH. Shut in.

14. I hereby certify that the foregoing is true and correct

Signed *[Signature]*

Title Production Clerk

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title

Date Oct. 26, 1994

ACCEPTED FOR RECORD
PETER W. CHESTER
Date

OCT 28 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side