Orm 9-331 May 1963) UNITED STATES SUBMIT IN TRIPLICATE. DEPARTMENT THE INTERIOR (Other instructions on Verse side)	Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM-0191401	
GEOLOGICAL SURVEY		
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.		
Use "APPLICATION FOR PERMIT-" for such proposals.)	TONIT AGEL MENT NA	ME
OIL GAS WELL OTHER Dry		
NAME OF OPERATOR	8. FARM OR LEASE NAM	
Union Texas Petroleum a Division of Allied Chemical Corporation	n Allen-Feder 9. WELL NO.	al
Box 1859 - Midland, Texas	1	
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)	10. FIELD AND POOL, OF	WILDCAT
At surface	Wildcat	
	11. BEC., T., B., M., OR B SURVEY OR ARDA	LE. IND
660' FS & WL Sec 12, T-8-S, R-31-E	Sec 12, T-8-5	5. R-31-E
4. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	
4320 DF	Chaves	New Mexic
6. Check Appropriate Box To Indicate Nature of Notice, Report, or Ot	her Data	
NOTICE OF INTENTION TO: SUBSEQUE	NT REPORT OF:	
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING W	
FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	ALTERING CA	<u> </u>
SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING	ABANDONMEN	т• XX
REPAIR WELL CHANGE PLANS (Other) (Other) (Note: Report results of Completion or Recompletion	f multiple completion (on Well
7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, i proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical nent to this work.) *	ncluding estimated date depths for all markers	e of starting any and zones perti-
(A) Squeezed perforations 4071 - 4124' W/125 sacks cement. Top	of cement 4065	51
	-	
(B) Spotted 25 sacks cement plug from 3765 - 4065'.		
(C) Shot off 4-1/2" casing @3200'.		
(D) Spotted 50 sacks cement plug from 3150 - 3250'.		
(E) Spotted 135 sack cement plug from 1950 - 2150'.		
(F) Spotted 30 sack cement plug from 349 - 399'.		
(G) Spotted 10 sack cement in top of surface and welded 4-1/2" m 1-23-65	arker on well.	
-		. ••••
		فر ا
8. I hereby certify that the foregoing is true and correct		- 07 - 20/:
SIGNED K. J. Strve TITLE District Superintendent		y 27, 196
(This space for Federal or State office use)		
(This space for Federal or State office use) APPROVED BY	APPR	OVED
APPROVED BY TITLE		OVED

ł

۰.