

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP!
(Other instructions
verse side)

TE-
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

RM-0356671

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL 10

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10, T15S, R31E

12. COUNTY OR PARISH

CHAVEZ

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
UNION OIL COMPANY OF CALIFORNIA

3. ADDRESS OF OPERATOR
619 West Texas Avenue, Midland, Texas 79704

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

EW/4 EW/4, 330' FWL & 330' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4398.4' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded at 4:00 P.M. 6-26-65 and drilled 11" hole to 396'.

Ran & cemented 383.16' 8-5/8", 20,24 & 32#, new & used casing at 395.15' with 250 sx. reg. cement with 4% gel & 2% CaCl added. Cement circulated. CIP at 9:00 P.M. 6-26-65. Waited on cement 18 hours. Tested casing with 1000# for 30 minutes. OK.

Drilled 6-3/4" hole to 3225' TD.

Ran & cemented 3214.11' 4-1/2", 9.5#, new casing at 3224' with 250 sx. reg. 4% gel cement followed by 50 sx. Incon cement. CIP at 3:05 P.M. 7-1-65. Waited on cement 18 hours. Tested casing with 1000# for 30 minutes. OK.

RECEIVED

JUL 1 1965

RECEIVED
JUL 14 1965

18. I hereby certify that the foregoing is true and correct

SIGNED

C. H. Dizon

TITLE

Production Clerk

DATE

July 12, 1965

(This space for Federal or State office use)

APPROVED BY

APPROVED

TITLE

DATE

JUL 1 1965

Rudolph C. Baier, Jr.
RUDOLPH C. BAIER, JR.
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.