

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
WC	OPR	WILLIAMSON, J. C.			MAP
		1 Reid, Elsie			
		Sec. 35, T-10-S, R-31-E			CO-ORD
		990' fr N Line & 1849' fr W Line of Sec.			
		Spd 4-13-65			
		CLASS			
		E [REDACTED]			
		Cmp 6-11-65			
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
8 5/8" 336' 150		Anhy 1587			
4 1/2" 4492' 250		Yates 2226			
		SA 3473			
LOGS EL GR RA IND HC A					
		TD 4500'			

PLUGGED & ABANDONED

2326
2356
76

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Sitton & Norton Drlg. Co.	PROP DEPTH	4500'	TYPE
DATE				

F.R. 4-15-65; Oper's Elev. 4427' Df.
PD 4500' - SA
Contractor - Sitton & Norton Drlg. Co.
4-19-65 Drlg. 1222' RB
4-26-65 Drlg. 4118'.
5-3-65 TD 4500', MO Rotary.
Cored 4348-80', rec 32' anhy dolo., w/sli
scatt shows.
5-10-65 TD 4500', SI.
Perf @ 4281', 4284', 4286', 4288', 4361',
4367', 4369', 4371', 4375', 4414', 4416',
4418' W/1 SPI
Ac. 600 gals.,
2000' fluid in hole.
Re-Ac. 6000 gals. 4281-4418'
Swbd 40 BAW (25% oil) & swbd dry.
5-17-65 TD 4500', SDO.
5-24-65 TD 4500', SDO.

CHAVES Wildcat NM Sec. 35-10S-31E
WILLIAMSON, J. C., #1 Reid, Elsie Page #2

██████-65 TD 4500', PBD 4492', SDO.
██████-65 TD 4500', PBD 4492', SDO.
6-14-65 TD 4500', PBD 4492', PLUGGED & ABANDONED.
Re-Tr. 1000 gals Kerosene + 1000 gals
acid 4281-4418'
Swbd load
Swbd salt wtr, w/tr. oil.