

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP DATE*
(Other instruction
reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

RM-0124983

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

James-Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Texas-Pennsylvanian

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24, T-8-S, R-32-E,

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Shell Oil Company (Western Division)

3. ADDRESS OF OPERATOR

P. O. Box 1509, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

**660' FSL and 1980' FSL (SE/4 SW/4) Section 24, T-8-S, R-32-E
MFM Survey, Chaves County, New Mexico**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4446' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

September 29, 1966 thru October 8, 1966.

1. Spotted 50 sacks cement, plug at base of Pennsylvanian perforations 3981' - 3989'.

2. Determined free point at 4100'.

3. Shot casing at 4112' and 4017'. Cut and pulled 4017' 5 1/2" casing.

4. Spotted the following cement plugs:

25 sx. top of 5 1/2" casing stub.

25 sx. 4950' - 4875' (top Glorieta 4932')

25 sx. at 3580' (Base of 8 3/8" casing)

10 sx. at surface.

5. Erected prescribed marker.

6. Plugged and abandoned October 8, 1966

18. I hereby certify that the foregoing is true and correct

Original Signed By:

SIGNED **R. J. Doubek**

R. J. Doubek

TITLE **Division Mechanical Engineer**

DATE **October 25, 1966**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

JUN 21 1967

*See Instructions on Reverse Side

**J L GORDON
ACTING DISTRICT ENGINEER**

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 7: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditions for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1964-O-685239

687-981

APPROVED
JUN 21 1964
FEDERAL BUREAU OF INVESTIGATION
U.S. DEPARTMENT OF JUSTICE