

COUNTY	HAYES	FIELD	Undesignated	STATE	NM
OPR	GREAT WESTERN DRILLING CO.				MAP
	1 Davis State				
	Sec 26, T-8-S, R-32-E				CO-ORD
	660' fr N Line & 1980' fr W Line of Sec.				
	Spd 9-10-65;				
	Opr 10-21-65;				
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING					
10 3/4" at 265' w/250 sx					
5/8" at 2600' w/600 sx					
LOGS EL GR RA IND HC A					
	TD 9140';				
PLUGGED & ABANDONED.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Loffland Bros.	PROP DEPTH	9100'	TYPE
DATE				

F.R. 9-2-65; Opr's Elev. 4425' KB
PD 9100' Bough "C"
Contractor - Loffland Bros.
9-13-65 Drig. 2645' shly & salt
9-20-65 Drig. 4906' lm
9-27-65 Drig. 7116' lm
10-4-65 Drig. 8190' lm & sh
10-11-65 Drig. 8681' lm
10-18-65 Coring @ 9068'
Cored 8990-9006', rec 16' being:
11' lm;
1' sh;
2' lm;
2' sh;

18-65 Continued
Cored 9006-43', rec 33' being:
3' sh;
5' lm;
1' sh;
14' lm;
4' sh;
6' lm;
Cored 9043-54', rec 10' sh;
10-25-65 TD 9140'; PLUGGED & ABANDONED
Cored 9054-57', rec 2' being:
1' lm;
1' sh;
Cored 9057-9110', rec 53' lm & sh w/poro filled
w/calcite 9092-9100', NS;

10-25-65 Continued
Cored 9110-40', rec 30' lm & sh, NS;
LOG TOPS: Anhydrite 1800', Yates 2357', Seven
Rivers 2545', Queen 3030', San Andres 3554',
San Andres Poro. 4283', Glorieta 4970', Tubb
6440', Abo 7290', Wolfcamp 8334', Three Bros.
8800', Bough "A" 8935', Bough "B" 9004', Bough
"C" 9048', Bough "D" 9071', Bough "E" 9103';