

CO-ORD

Spd 10-6-65

CLASS

EL

Cmp 12-4-65

SX . TUBING

- SG & SX . TUBING

FORMATION

DATUM

FORMATION

DATUM

13 3/8" 346" 350

8 5/8" 3600" 200

4 1/2" 4540" 200

LOGS EL GR RA IND HC A

TD 9110'

PLUGGED & ABANDONED

CONT.
DATE

PROP DEPTH 9200'

TYPE

(Orig. The Atlantic Refg. Co., #1 Sumerlin,
Abandoned Location 8-2-65)

10-11-65 TD 3600', running casing.

10-18-65 Drlg. 5573'.

Cored 4354-4400', rec 46' dolo & lm., w/
tr. oil & wtr in frags.

DST 4230-4400', open 1 hr 45 mins,

rec 2' DM, w/tr. oil + 390' DM,

1 hr ISTP 1492#, FP 137-298#.

1 hr FSIP 1331#.

10-18-65 Cont.
 Cored 4452-4510', rec 58' dolo., w/sli
 show cil 4457-89'.
 DST 4423-4510', open 1 hr 45 mins.
 rec 240' DM, w/tr. cil + 90' wtr,
 1 hr ISIP 1513#, FP 85-213#,
 1 hr FSIP 1344#.

10-25-65 Drlg. 7816' lm & sh.

11-1-65 Drlg. 8837'.

11-8-65 TD 9110', PBD 4524', prep to perf.
 SP DST 9010-50', open 1 hr,
 rec 15' DM,
 1 hr ISIP 69#, FP 45-46#,
 2 hr FSIP 69#

11-15-65 TD 9110', PBD 4524', AC Comp. Drill.

11-22-65 TD 9110', PBD 4524', CO Sand

Perf @ 4343', 4353', 4357', 4360',
 4366', 4382', 4387', 4392', 4398'
 W/1 SPI

Set Straddle Fkrs @ 4343' & 4398'

Ac (4343-4398') 500 gals acid

Swbd acid wtr (no new fluid)

Perf @ 4281', 4289', 4301', 4309',
 4327', 4424', 4435', 4478', 4481',
 4485' W/1 SPI

Ac (4281-4485') 1500 gals.

Frac (4281-4485') 25,000 gals wtr +
 25,000# sd.

11-29-65 TD 9110', PBD 4524', SDO.
 Swbd dry (4281-4485')

12-6-65 TD 9110', PBD 4524', PLUGGED & ABANDONED.

CHAVES Tobac-Penn. NM Sec. 19-85-33E
SOUTHERN PET. EXPL., INC., #1 Sumnerlin, Guy Page #2

12-6-65 Cont.
LOG TOPS: Yates 2350', SA 3560', Glorieta
4960', Tubb 6435', Abo 7300', Wolfcamp
8300' (?), Bough "C" 9003',
6-6-r6 RE-ISSUED TO SHOW ADDITIONAL INFORMATION.