

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
OPR	CACTUS DRILLING COMPANY				MAP
1 Gary-Federal					
Sec. 8, T-8-S, R-32-E				CO-ORD	
660' FSL, 660' FWL of Sec.				MC 10411	
Spd 2-14-66		CLASS		EL	
Cmp 4-28-66		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8" 387' 200					
4 1/2" 4250' 150					
LOGS EL GR RA IND HC A					
		TD 4285'			

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Co. Tools	PROP DEPTH	4500'	TYPE
DATE			

F.R. 2-17-66
PD 4500' - SA
Contractor - Company Tools
2-21-66 Drlg. 3735'.
2-28-66 TD 4285', WOC.
Cored 4150-4200', rec 48' being:
18' dolo., w/anhydritic incls., NS;
7' dolo., w/bldg oil & wtr;
13' dolo., w/NS; 10' dolo & anhy.,
bldg oil & wtr.
Cored 4200-50', rec 50' dolo & anhy.,
w/scatt shows.
Cored 4250-85', rec 35' same.
3-7-66 TD 4285', PBD 4215', prep to test on pump.
Perf @ 4235', 4239', 4241' W/2 SPI
Ac (4235-41') 500 gals.
Swbd dry

3-7-66 Continued
Set BP @ 4215'
Perf 4167-70', 4187-88' W/2 SPF
Ac (4167-88') 500 gals.
Swbd dry
Ac (4167-88') 2000 gals.
Swbd 4 BFPH (20% oil)
3-14-66 TD 4285', PBD 4215', RU Heater Treater.
Pmpd 100 BFPD (20% oil)
3-21-66 TD 4285', PBD 4215', tstg on pump (no gauge)
3-28-66 TD 4285', PBD 4215', tstg on pump.
Pmpd 11 BO + 100 BW/24 hrs.
4-4-66 TD 4285', PBD 4215', tstg on pump.
Pmpd 5 BO + 100 BW/24 hrs.
4-11-66 TD 4285', PBD 4215', tstg on pump.
Pmpd 5 BO + 75 BW/24 hrs.

4-18-66 TD 4285', PBD 4182', swbg.
Set BP @ 4145'
Perf 4096-98', 4105-07' W/2 SPF
Ac (4096-4107') 2000 gals;
Channeled
Squeezed perfs 4096-4107' W/100 sx.
Drld out BP @ 4145'
Set BP @ 4182'
Perf 4166-70' W/2 SPF
Ac (4166-70') 500 gals.
4-25-66 TD 4285', PBD 4182', prep to P&A.
Att. to swab perfs 4166-70' &
Had Communications
5-2-66 TD 4285', PBD 4182', PLUGGED & ABANDONED.
LOG TOP: San Andres 3349'.