

COUNTY	CHAVES		FIELD	Chaveroo		STATE	NM	
OPR	CHAMPLIN PETROLEUM COMPANY						MAP	
	1 State 5 "A"							
	Sec. 5, T-8-S, R-33-E						CO-ORD	
	660' FNL, 1980' FWL of Sec.						MC 10434	
	Spd 3-21-66		CLASS			EL		
	Temp 4-19-66		FORMATION	DATUM	FORMATION	DATUM		
SG & SX - TUBING								
8 5/8" 374' 250								
4 1/2" 4430' 250								
LOGS EL GR RA IND HC A								
			TD 4430'					

IP San Andres Perfs 4116-4298' Pmpd 44 BOPD + 81 BW. Pot. Based on 24 hr test, gravity 24.6, GOR 760.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT	Sitton & Norton	PROP DEPTH	4500'	TYPE
DATE				

F.R. 3-17-66' Opr's Elev. 4433' GL
PD 4500' - SA
Contractor - Sitton & Norton
3-28-66 Drlg. 4244'.
4-4-66 TD 4430', rec'g load.
Perf @ 4116', 4135', 4166', 4198', 4218',
4230', 4235', 4258', 4293', 4298' W/2 SPI
Ac (4116-4298') 2500 gals.
Frac (4116-4298') 50,000 gals wtr +
40,000# sd.
4-11-66 TD 4430', pmpg load. (-951 BLW)
4-18-66 TD 4430', pmpg load.
4-25-66 TD 4430', COMPLETED.
(Holding for tops)
5-2-66 TD 4430', Completion Reported.
LOG TOPS: Anhydrite 1842', Salt 1914',
Yates 2342', Queen 3012', San Andres 3575'.