

COUNTY	CHAVES	FIELD	Chavez	STATE	NM
OPR	CHAMPLIN PETROLEUM COMPANY				
	2 State 3 "A"				
	Sec. 3, T-8-S, R-33-E				
	660' FWL, 660' FWL of Sec.				
	Spd 4-28-66				
	Cmp 5-16-66				
CSG & SX - TUBING		CLASS		EL	
		FORMATION	DATUM	FORMATION	DATUM
8 5/8" 366' 250					
4 1/2" 4435' 325					
LOGS EL GR RA IND HC A		TD 4435'			

IP San Andres Perfs 4211-4400' Subd 74 BOPD + 74 BW. Pot. Based on 24 hr test, gravity 24.6, ROE ASTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton
DATE
PROP DEPTH 4500' TYPE

F.R. 3-24-66; Cpr's Elev. 4433' GL
PD 4500' - SA
Contractor - Sitton & Norton
5-2-66 Drig. 3580'.
5-9-66 TD 4435', prep to perf.
5-23-66 TD 4435', testing on pump.
Perf @ 4211', 423', 4263', 4293', 4308',
4317', 432', 4352', 4400' w/2 SPY
Ac (4211-4400') 500 gals.
Frac (4211-4400') 50,000 gals gel. + 40,000# sd.
5-31-66 TD 4435', COMPLETE.
ICG TOPS: Anhydrite 1890', Salt 1316',
Queen 3008', San Andres 2570'.