

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
OPR	CHAMPLIN PETROLEUM COMPANY				MAP
1	Signal-State				
Sec. 1	T-8-S, R-32-E				CO-ORD
660'	FNL, 660' FEL of Sec.				MC 10438
Spd 4-1-66	CLASS				ES
Cmp 5-2-66	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING					
8 5/8" 369' 250					
4 1/2" 4450' 325					
LOGS EL GR RA IND HC A					
	TD 4692', PBD 4395'				

IP San Andres Perfs 4169-4291' Pmpd 45 BOPD + 75 BW. Pot.
Based on 24 hr test, gravity 24.6, GOR 780.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton	PROP DEPTH 4700'	TYPE
DATE		

F.R. 3-31-66
PD 4700' - SA
Contractor - Sitton & Norton
4-4-66 Drlg. 3524' lm.
4-11-66 Drlg. 4506' dolo.
DST 4082-4235', open 1 hr 30 mins,
Rec 35' Drlg Mud,
1 hr ISIP 192#, FP 106-106#,
1 hr 30 min FSIP 181#.
DST 4242-4365', open 1 hr 30 mins,
Rec 30' free oil, 218' HO&GCM +
196' Oil & Sul Wtr CM (65% sul wtr)
1 hr ISIP 1331#, FP 103-254#,
1 hr 30 min FSIP 1286#.

CHAVES Wildcat NM Sec. 1-8S-32E
CHAMPLIN PETROLEUM CO., #1 Signal-State Page #2

4-18-66 TD 4692', PBD 4395', RU Pump.
Perf @ 4169', 4179', 4262', 4272', 4281',
4287', 4291' W/2 SPI
Frac (4169-4291') 50,000 gals wtr +
40,000# sd.
4-25-66 TD 4692', PBD 4395', pmpg load. (-900 BLW)
5-2-66 TD 4692', PBD 4395', pmpg load.
5-9-66 TD 4692', PBD 4395', COMPLETE.
LOG TOP: Pi Zone 4020' (+436')