DISTRIBUTION NEW MEXICO OIL CONSERWADING MADE SOS. C. HAY 2 8 02 M '66 Soll Middle of the conservation	NO. OF COPIES RECEIVED				Form C-103	.,,,
NEW MEXICO OIL CONSERVACION COMBINE CONTROL PROPERTY OF MANY 2 8 02 MM '66 Control		 			•	
May 2 8 02 M '66 Set Editions Type of Large Set Edition of your Support Notices Set Se		NEW MEXIC	CO OIL CONSERVATES	ебмивоов. С.		
U.S. CORRECT BUILDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SOUTHER TO COMMENT OFFICE OF			ing production of the same of	_		
DOWNERS ON SUNDRY NOTICES AND REPORTS ON WELLS DOWNERS OF THE PROPERTY OF THE	U.S.G.S.		May 2	8 oz AM '66		
SUNDRY NOTICES AND REPORTS ON WELLS (10 NOT USE THE ADMINISTRATE SECURITY FOR PRINTING COLOUTY ON WELLS (20 NOT USE THE ADMINISTRATE SECURITY FOR PRINTING COLOUTY ON WELLS (20 NOT USE THE ADMINISTRATE SECURITY FOR PRINTING COLOUTY ON WELLS (20 NOT USE THE ADMINISTRATE SECURITY OF PRINTING COLOUTY ON WELLS (20 NOT USE THE ADMINISTRATE SECURITY OF PRINTING COLOUTY OF THE ADMINISTRATE OF THE ADMINISTR	LAND OFFICE		iini S	• • • • • • • • • • • • • • • • • • •		
(SO DOT 187 THE SUMPLY NOTICES AND REPORTS ON WELLS THE STATE OF THE SUMPLY OF PRINCE STATE OF THE STATE OF	OPERATOR					
The second Proposed Southern Petroleum Exploration, Inc. 3. Address of Operator Box 1934, Roswell, New Mexico 4. Location of well B 1980 FEET FROM FIRE 1980 FEET FROM FIRE FROM FIRE FROM FIRE FROM FROM FROM FROM FROM FROM FROM FROM					mmm	mmin
The state of Completed Systems of Completed Systems and Completed	S (DO NOT USE THIS FORM	UNDRY NOTICES AND RI	EPORTS ON WELLS EEPEN OR PLUG BACK TO A DIF C-101) FOR SUCH PROPOSALS	FERENT RESERVOIR.		
2. Name of Coperator Southern Petroleum Exploration, Inc. 3. Name of Coperator Southern Petroleum Exploration, Inc. 4. Addiess of Coperator Southern Petroleum Exploration, Inc. 5. Name of Coperator Southern Petroleum Exploration, Inc. 660 Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Notice of Intention To: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PLUS AND ARABODINI TILBORANIV PARSON CHANGE PLANS CHANGE	1.	PETCATION FOR PERMIT = (FORM	0-101) 1 00 0001 1 100 000	·	1 ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	
2. State I Southern Petroleum Exploration, Inc. 3. Address of Operator Box 1474, Roswell, New Mexico 4. Location of Well West Line, SECTION 19. Elevand Fool, or Wildow Chaveroo FELT MON THE West Line, SECTION 19. Elevand Fool, or Wildow Chaveroo FILE AND ASSA 33-E NAMED	WELL WELL	OTHER-				
States of operation of Well E 1980 North 660 West Line, SECTION 1 FEET FROM THE SECTION Show whether DF, RT, GR, etc) THE WEST LINE, SECTION 1 FEET FROM THE SECTION Show whether DF, RT, GR, etc) THE WEST LINE, SECTION 1 FEET FROM THE SECTION SHOW whether DF, RT, GR, etc) THE WEST LINE, SECTION 1 FEET FROM THE SECTION SHOW whether DF, RT, GR, etc) THE WEST LINE, SECTION 1 FEET FROM THE SECTION SHOW whether DF, RT, GR, etc) THE WEST LINE, SECTION 1 FEET FROM THE SECTION SHOW WHITE CONTINUE OF THE SECTION SHOW WHITE CONTINUE CON	2. Name of Operator Southern Petrole	um Exploration, In	ie.			
4. Location of Well West THE LINE, SECTION West THE LINE, SECTION THE COMMENT AND WHATHER DEPARTMENT OF SOME	3. Address of Operator	l New Mexico			1 ''	
West West 1. INC. SECTION TO THE TROWN THE TOWNSHIP Show whether DF, RT, GR, etc.) 15. Elevation Show whether DF, RT, GR, etc.) 4416 GR. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PLEF ORM REMEDIAL WORK TEMPORABLY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed a Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703. Ban 4478' of 4-1/2", 10.50%, J-55, Lonestar new easing. Cemented with 350 sacks Insor Pos w/2% gel. and 8% salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.H. 4-24-66. Waited 18 hours for cement to set. Tested casing with 10007 for 30 minutes. Held O.K. Temperature survey found 16. I bereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 18. I bereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 18. I bereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 18. I bereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 18. I bereby certify that the information above is true and complete to the best of my knowledge and belief. PLIST THE TOWNSHIP						•
15. Elevation (Show whether DF, NT, CR, etc.) 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: PERFORM MEMORIAL WORK PLUG AND ABANDON PLUG AN	E	1980				•
TOWNSHIP TOWNSHIP TOWNSHIP 15. Elevation (Show whether DF, RT, GR, etc.) (A416 GR. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: PERFORM HEMEDIAL WORK TEMPORALITY ARABON PULLS AND ABANDON PULL AND ABANDON PULL AND ABANDON TEMPORALITY ARABON OTHER 17. Describe Proposed of Completed Operations (Clearly state all pertiaent details, and give pertiaent dates, including estimated date of starting any propose work) SEE NULE 1703. Ram 4478: of 4-1/2m, 10.50%, J-55, Lonestar new casing. Comented with 350 macks Insor Poz w/2% gels and 8% salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for coment to set. Tested casing with 1000% for 30 minutes. Held 0.K. Temperature survey found top of cement at 3700 for the set of my knowledge and belief. District Land Manager 18. Thereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 19. Company Chartes Altering Easing Fulls AND ABANDONNELLY Fulls AND ABANDONNELLY COMMENCE BRICLING OPHS. Altering Easing Altering Easing Fulls AND ABANDONNELLY Altering Easing Fulls AND ABANDONNELLY Full			8_8	33-E		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ATER CASING OTHER OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work; see Rule 1703. Ran 4478 of 4-1/2", 10.50%, J-55, Lonestar new casing. Cemented with 350 sacks Incor Pos w/2% gel. and 8% salt per sack. Used guide shoe and float valve - 6 centralisers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested casing with 1000% for 30 minutes. Held O.K. Temperature survey found top of cement at 3700 of cement at 3700 of cement to set. District Land Manager NATE District Land Manager		, SECTION TOWN	NSHIPRANG	ENM	PM. ()	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM MEMERIAL WORK PULS AND ABANDON PULL ON ALTER CASING OTHER OTHER 17. Demertise Proposed or Completed Operations (Clearly state all pertiaent details, and give pertinent dates, including estimated date of storting any propose work) size Rule tros. Pan 4478: of 4-1/2", 10.50%, J-55, Lonestar new casing. Cemented with 350 sacks Incor Poz w/2% gel. and 8% salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested casing with 1000% for 30 minutes. Held O.K. Temperature survey found top of cement at 3700° III. I hereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager		TTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTT	(Show whather DE RT CR	etc. l	12. County	<i>HHHH</i>
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Discribe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SER RULE 1103. Ran 4478* of 4-1/2", 10.50#, J-55, Lonestar new casing. Cemented with 350 sacks Insor Poz w/2% gel. and 8# salt per sack. Used guide shoe and float valve - 6 centralisers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested casing with 1000# for 30 minutes. Held 0.K. Temperature survey found top of cement at 37001* 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager ALTERING CASING AL		15. Elevation	6 GR.	, (,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
PERFORM REMEDIAL NORK TEMPORABILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) see Rule 103. Ram 4478' of 4-1/2", 10.50#, J-55, Lonestar new casing. Comented with 350 sacks Insor Pos w/2% gel. and 8# salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested casing with 1000# for 30 minutes. Held 0.K. Temperature survey found top of cement at 37001** District Land Manager 18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 4-29-66			- I. li Noture of	Notice Penant on	Other Data	
PEUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOS PLUG AND ABANDONMENT OTHER COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOS PLUG AND ABANDONMENT 17. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1903. Ran 4478* of 4-1/2", 10.50%, J-55, Lonestar new casing. Commented with 350 sacks Incor Pos w/2% gel. and 8% salt per sack. Used guide shoe and float valve - 6 centralisers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested casing with 1000% for 30 minutes. Held O.K. Temperature survey found top of cement at 37001** 16.1 bereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager Alterine Casing Anandomment Comment of Complete Land Manager Alterine Casing Plug And Abandomment Comment of Complete Land Manager Alterine Casing Plug And Abandomment Comment of Complete Comment details, and give pertinent details, and giv			o Indicate Nature of	SUBSEQUE	ENT REPORT OF	:
PULL OR ALTER CASING OTHER O				·		
COMMERCE ORILLING OWS. CASING TEST AND CEMENT JOB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) see rule. 103. Ran 4478° of 4-1/2", 10.50%, J-55, Lonestar new casing. Cemented with 350 sacks Incor Por w/2% gel. and 8% salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested casing with 1000% for 30 minutes. Held 0.K. Temperature survey found top of cement at 3700°. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 19. Distri	PERFORM REMEDIAL WORK	PLUG AN	ID ABANDON REMEDIAL	WORK		-
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposes work) see Rule 1103. Ram 4478' of 4-1/2", 10.50%, J-55, Lonestar new easing. Cemented with 350 sacks Incor Pez w/2% gel. and 8% salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested casing with 1000% for 30 minutes. Held 0.K. Temperature survey found top of cement at 3700 1 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager A-29-66				===	PLUG	AND ABANDONMENT
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703. Ran 4478' of 4-1/2", 10.50#, J-55, Lonestar new easing. Cemented with 350 sacks Insor Pos w/2% gel. and 8# salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for cement to set. Tested easing with 1000# for 30 minutes. Held O.K. Temperature survey found top of cement at 37000** 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager District Land Manager District Land Manager	PULL OR ALTER CASING	CHANGE	PLANS CASING TE	ST AND CEMENT JOB		_
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.			OTHER.			
Ran 4478' of 4-1/2", 10.50#, J-55, Lonestar new casing. Comented with 350 sacks Insor Poz w/2% gel. and 8# salt per sack. Used guide shoe and float valve - 6 centralizers. Plug down 3:15 A.M. 4-24-66. Waited 18 hours for coment to set. Tested casing with 1000# for 30 minutes. Held 0.K. Temperature survey found top of cement at 3700. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. District Land Manager 19. 10.50# 19. 1	OTHER					
SIGNED BL. Lich District Land Manager 4-29-66	Incor Poz w/2% centralizers. Tested casing w	gel. and 8# salt Plug down 3:15 A. dth 1000# for 30 :	per sack. Use d M. 4-24-66. Wai	guide shoe as ted 18 hours	for cement t	co set.
SIGNED	18. I hereby certify that the inf	formation above is true and comp	District			29-66
	STANED					
		7		*		₽ ; ₹

APPROVED BY ___

CONDITIONS OF APPROVAL, IF ANY:

₹... ₹...

•