

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

MAY 6 2 52 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG 1195	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator Atlantic Richfield Company (Formerly The Atlantic Refining Company)		8. Farm or Lease Name State "BF"
3. Address of Operator P. O. Box 1978, Roswell, N.M.		9. Well No. 2
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 8-S RANGE 33-E NMPM.		10. Field and Pool, or Wildcat Chaveroo-San Andres
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Chaves

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 4:30 PM 5/2/66. Drilled 12-1/4" hole to 371'. Ran 11 jts 8-5/8" OD 8R 24# J-55 casing w/float collar & guide shoe = 356.31'. Set at 367.66'. Cemented w/255 sx Incor Neat cement + 2% CaCl. Plug down at 7:30 PM 5/2/66. Cement circulated. NU casinghead & BOP's. Tested 8-5/8" casing to 1000# for 30 min. OK & job complete at 2:30 PM 5/3/66 after WOC 19 hrs. Resumed drilling - 7-7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed

O. D. Bretches

SIGNED TITLE **Dist. Drilling Supervisor** DATE **5-5-66**

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: