COUNTY CHAVES FIELD Chaveroo STATE NM

OPR CHAMPLIN PETROLEUM CO.

1 State 6-8-33 MAP

Sec. 6, T-8-S, R-33-E

660' FNL, 660' FWL of Sec. CO-ORD

Spd 5-7-66 MC 10444

Cmp 5-20-66 CLASS B[redacted]

CSG & SX - TUBING

8 5/8" 373' 250
4 1/2" 4403' 325

LOGS EL GR RA IND HC A

FORMATION	DATUM	FORMATION	DATUM

TD 4403'

IP San Andres Perfs 4183-4333' Swbd 48 BOPD + 193 BW. Pot. based on 24 hr test, gravity 24.6, GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton

DATE PROP DEPTH 4500' TYPE

4474
3552
922
70
992

F.E. 5-12-66, Opr's Elev. 4474' DF
PD 4500' - SA
Contractor - Sitton & Norton
5-23-66 TD 4403', swbg load.
Perf @ 4183', 4210', 4234', 4238', 4266', 4274', 4288', 4299', 4305', 4314', 4333' W/2 SPF
Ac (4183-4333') 500 gals.
Frac (4183-4333') 50,000 gals gelled wtr w 40,000# sd.
5-31-66 TD 4403', COMPLETE.
LOG TOPS: Anhydrite 1775', Yates 2332', Queen 2989', San Andres 3352'.