

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
OPR	INGRAM, TOM L.				MAP
	1 State A				
	Sec. 26, T-8-S, R-32-E				CO-ORD
	660' FSL, 1980' FEL of Sec.				MC 10445
	Spd 5-14-66				EL
	Cmp 11-28-66				CLASS
	FORMATION		DATUM		
CSG & SX - TUBING					
8 5/8" 350' 135					
4 1/2" 4400' 600					
LOGS EL GR RA IND HC A					
	TD 4400', PBD 4248'				
IP San Andres Perfs 4242-46' Pmpd 2 BOPD + 165 BW. Pot. Based on 24 hr test.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Verna Drlg. Co. PROP DEPTH 4500' TYPE
DATE

F.R. 5-19-66; Opr's Elev. 4412' GL
PD 4500' - SA
Contractor - Verna

7-14-66 AMEND OPERATOR & LEASE DESIGNATION: Formerly Wilbanks & Rasmussen, #1 Atlantic-State.

8-18-66 AMEND OPERATOR & LEASE DESIGNATION: Formerly Humble Oil & Refg. Co., #1 New Mexico BY State.

5-23-66 TD 350', prep to run csg.

5-31-66 Drlg. 1780' anhy & salt.

6-6-66 Drlg. 4196'.

6-13-66 TD 4400', WOC.
Cored 4235-78', rec 40' lm & anhy., w/show oil & wtr.
Cored 4278-4328', rec 50' lm & anhy., w/show oil & wtr.

6-20-66 TD 4400', swbg.
Perf @ 4232', 4238', 4242', 4247', 4252', 4258', 4262', 4274', 4278', 4284' W/1 SP
Acid (4232-84') 2250 gals.

6-20-66 Cont.
Swbd 42 BL&AW + 38 BFW, w/tr. oil in 9 hrs.
Swbd 95 BW, w/sli show oil in 9 hrs.
6-27-66 TD 4400', TO Pump.
Pmpd 160 BW, w/tr. oil in 24 hrs.
7-5-66 TD 4400', TO Pump.
Pmpd 155 BW, w/tr. oil in 24 hrs.
7-11-66 TD 4400', TO Pump.
Pmpd 158 BW, w/sli tr. oil in 24 hrs.
7-18-66 TD 4400', SI.
Pmpd 162 BW, w/very sli show oil in 24 hrs.
7-25-66 TD 4400', SI.
8-1-66 TD 4400', SI.
8-8-66 TD 4400', DO to 4253', prep perf.
Squeezed perfs 4232-84' W/100 sx.
Drld out to 4253'

8-15-66 TD 4400', PBD 4253', SI.
Perf @ 4232', 4237', 4240', 4242', 4244',
4246', 4248', 4250', 4252' W/1 SPI
Swbd dry
Acid (4232-52') 500 gals.
Swbd acid wtr, w/sli show oil & gas (4232-52')
SI for 16 hrs.
Swbd 5-6 BFPH (2% oil) for 7 hrs (4232-52')
8-22-66 TD 4400', PBD 4253', SI.
8-29-66 TD 4400', PBD 4248', SI.
Squeezed perfs 4232-52' W/100 sx.
Drld out to 4248'
Perf @ 4242', 4243', 4245', 4246' W/1 SPI
Acid (4242-46') 500 gals.
Swbd dry, w/sli show oil (4242-46')