

COUNTY	CHAVES	FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PETROLEUM COMPANY				MAP
	2 State 6-8-33				
	Sec. 6, T-8-S, R-33-E				CO-ORD
	1980' FNL, 660' FWL of Sec.				MC 10451
	Spd 5-25-66				
	Cmp 6-12-66				
	FORMATION		DATUM		
CSG & SX - TUBING					
8 5/8" 362' 250					
4 1/2" 4405' 325					
LOGS EL GR RA IND HC A					
	TD 4405', PBD 4403'				
IP San Andres Perfs 4194-4320' Pmpd 50 BOPD + 70 BW. Pot. Based on 24 hr test, TP 22#, CP 50#, Gravity 25., GOR 618.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Sitton & Norton	PROP DEPTH	4500'	TYPE
DATE				

F.R. 5-26-66
PD 4500' - SA
Contractor - Sitton & Norton

5-31-66 Drlg. 4068'.
6-6-66 TD 4405', prep to perf.
6-13-66 TD 4405', PBD 4403', RU Pump.
Perf @ 4194', 4208', 4220', 4240', 4286',
4291', 4300', 4308', 4314', 4320' W/2 SPI
Ac (4194-4320') 500 gals
Frac (4194-4320') 50,000 gals wtr +
40,000# sd.

6-20-66 TD 4405', PBD 4403', WO Pot.
Pmpd 50 BO + 70 BW/24 hrs, Gravity 25.,
GOR 618.

6-27-66 TD 4405', PBD 4403', COMPLETE.
LOG TOPS: Anhydrite 1773', Yates 2320',
Queen 2986', San Andres 3556'.