

COUNTY	CHAVES	FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PETROLEUM CO.				
	4	State	"6"	CO-ORD	
	Sec. 6, T-8-S, R-33-E				MC 10457
	1980' FSL, 660' FWL of Sec.				
	Spd 6-19-66				
	Cmp 8-4-66				
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING					
8 5/8" 383' 250					
4 1/2" 4405' 325					
LOGS EL GR RA IND HC A	TD 4405', PBD 4403'				

TP San Andres Perfs 4153-4314' Pmpd 14 BOPD + 305 BW. Pot. Based on 24 hr test, TP 14#, CP 75#, gravity 25.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton
DATE
PROP DEPTH 4500' TYPE

F.R. 6-2-66
PD 4500' - SA
Contractor - Sitton & Norton
6-30-66 AMEND LOCATION: Formerly 1980' FNL, 1980' FWL of Sec.
6-27-66 Drlg. 3036' 1m.
7-5-66 TD 4405', PBD 4403', prep to frac.
Perf @ 4153', 4187', 4195', 4210', 4265', 4287' W/2 SPI
Perf @ 4291', 4294', 4300', 4302', 4305', 4308', 4310', 4314' W/1 SPI
7-11-66 TD 4405', PBD 4403', pmpg load.
Acid (4153-4314') 500 gals.
Frac (4153-4314') 50,000 gals wtr + 40,000# sd.
7-18-66 TD 4405', PBD 4403', pmpg load.
Pmpd 130 BF (4% oil) in 24 hrs.

CHAVES Chavero NM
CHAMPLIN PETROLEUM CO., #6 State "6"

Sec. 6-8S-33E

Page #2

7-25-66 TD 4405', PED 4403', tstg on pump.
1-66 TD 4405', PED 4403', tstg on pump.
-66 TD 4405', PED 4403', tstg on pump.
8-15-66 TD 4405', PED 4403', tstg on pump.
8-22-66 TD 4405', PED 4403', tstg on pump.
8-29-66 TD 4405', PED 4403', COMPLETE.
LOG TOPS: Yates 2318', San Andres
3567'.