

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	K-527

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input type="checkbox"/> OTHER- Drilling Well	7. Unit Agreement Name
2. Name of Operator Southern Minerals Corporation	8. Farm or Lease Name State "C"
3. Address of Operator P. O. Box 716, Corpus Christi, Texas 78403	9. Well No. 3-4
4. Location of Well UNIT LETTER H 660 FEET FROM THE east LINE AND 1,980 FEET FROM THE north LINE, SECTION 2 TOWNSHIP 8-S RANGE 33-E NMPM.	10. Field and Pool, or Wildcat Chaveroo
15. Elevation (Show whether DF, RT, GR, etc.) 4345.9 GR	12. County Chaves

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- I. June 19, 1966. Spudded 11:30 p.m., drilled 11" hole to 360'. Set 8-5/8" o.d. 24#, J-55 casing at 360'. Cemented with 250 sacks Halliburton Common Cement with 2% calcium chloride. Cement circulated to surface. Plug down at 6:45 a.m., June 20, 1966. Waited 18 hours, tested casing with 1000# for 30 minutes. No bleed off of pressure.
- II. June 28, 1966. Drilled 7-7/8" hole to 4500'. Reached 4500' at 8:45 a.m., set 4-1/2", 10.50#, J-55 Casing at 4500'. Cemented with 375 sacks Incoor 50-50 Pozmix "A", with 2% Gel and 8# salt per sack. Plug on bottom at 7:00 a.m. June 30, 1966. Still waiting on casing at 7:00 a.m., July 6, 1966. Circulated top of cement at 2360'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED V. F. Harrison TITLE Vice President DATE July 6, 1966

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: