

COUNTY	CPAVES	FIELD	Chaveroo	STATE	NM
OPR	SOUTHERN MINERALS CORPORATION				MAP
State "C"					
Sec. 1, T-8-S, R-33-E					
660' FNL, 660' FWL of Sec.				CO-ORD	
Spd 7-1-66				MC 10465	
Cmp 8-1-66				CLASS	EL
CSG & SX - TUBING		FORMATION	DATUM	FORMATION	DATUM
8 5/8" 375' 250					
4 1/2" 4492' 375					
LOGS EL GR RA IND HC A					
		TD 4500', PBD 4492'			

IP San Andres Perfs 4244-4338' Pmpd 75 BOPD, + 32 BW. Pot. Based on 24 hr test, TP 125#, CP 50#, Gravity 26.8, GOR 200.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4800'	TYPE
DATE			

F.R. 6-23-66
PD 4800' - SA
7-5-66 Drlg. 3459' anhy.
7-11-66 TD 4500', running logs.
7-18-66 TD 4500', PBD 4492', flwg load.
Perf @ 4244', 4248', 4267', 4273', 4301',
4315', 4329', 4334', 4338' W/1 SPI
Acid (4244-4338') 2100 gals.
Frac (4244-4338') 40,000 gals oil +
40,000# sd.
Flwd 89 BLO/8 hrs thru 30/64" chk.
7-26-66 TD 4500', RJ Pump.
8-1-66 TD 4500', PBD 4492', tstg on pump.
Pmpd 6 BFPH (60% oil, 40% wtr)
8-8-66 TD 4500', PBD 4492', tstg on pump.
Pmpd 100 BO + 30 BW/24 hrs.
8-15-66 TD 4500', PBD 4492', WO OCC Potential.
Pmpd 75 BO + 32 BW/24 hrs, GOR 200.
8-29-66 TD 4500', PBD 4492', COMPLETE.
LOG TOPS: Anhydrite 1916', San Andres 3498'.