

NMOCC - ARTESIA

NMOCC - HOBBS

BLM - SANTA FE

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 0403706

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ABKO FEDERAL

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

CATO SAN ANDRES

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

10-8-30 NMPM

12. COUNTY OR PARISH

CHAVES

13. STATE

N.M.

1. OIL ☒ GAS ☐ OTHER ☐
WELL WELL WELL

2. NAME OF OPERATOR

San American Petroleum Corp.

3. ADDRESS OF OPERATOR

Box 68 Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL x 660' FEL, SEC 10 (UNIT H, SE 1/4 NE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

4118' R.D. 13.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

TD-3700: On 7-10-66, 4 1/2" OD 9.5" J-55 casing was set
at 3700' w/ 500 sx 12% GEL Ducon + 300 sq. neat.
Tested casing w/ 3000 psi for 30 minutes. Test
O.K. Perforated 3488-92, 3498-3504, 10-17, 26-29, 32-37,
49-58, 72-74 w/ 2SPF, Acidized w/ 2000 gallons and
Gravel w/ 30,000 gal oil, 40,500 # sand, 3000 # beads.
Evaluated, Dry. Set CIBP @ 3470 & Agg 3488-3574
w/ 100 sq. Perforated intervals 3344-66, 3400-44
w/ 1SPF. Acidized w/ 7000 gal acid. Evaluated.

On PT, swab: Flow 263 BO, 15 BLW, 74 BNW in 24 hours.

TD-3700

Comp. 7-27-66

PRD-3470

TPAY-3344-San Andres

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt

DATE

7-29-66

(This space for Federal or State office use)

APPROVED BY


CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

0+4 USGS-ROSWELL
1-SUSP
1-RAY
1-NSW

*See Instructions on Reverse Side



AUG 3 1966

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO