

COUNTY	CHAVES	FIELD	Cato-San Andres	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.				MAP
	1 ABKO-Federal				
	Sec. 10, T-8-S, R-30-E				CO-ORD
	1980' FNL, 660' FEL of Sec.				MC 10473
	Spd 7-1-66				
	Cmp 7-14-66				
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8" 452' 300					
4 1/2" 3700' 800					
LOGS EL GR RA IND HC A					
TD 3700', PBD 3470'					

IP San Andres Perfs 3344-3444' Swbd & Flwd 263 BOPD + 74. B Salt
Wtr. Pot. Based on 24 hr test, gravity 27., GOR 500.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH	4400'	TYPE
DATE			

F.R. 7-7-66; Opr's Elev. 4118' KB
PD 4400' - SA
Contractor - Cactus Drlg. Co.
7-6-66 Drlg. 2817'.
7-11-66 TD 3700', prep to perf.
7-16-66 TD 3700', PBD 3662', swbg.
Perf 3488-92', 3498-3504', 3510-17', 3526-29', 3532-37', 3549-58', 3572-84' W/2 SPF
Acid (3488-3584') 2000 gals; IR 4.7 BPM
Swbd 42 BLW, w/tr. oil in 12 hrs.
8-1-66 TD 3700', PBD 3470', COMPLETE.
Frac (3488-3584') 30,000 gals oil + 45,000#
sd. + 3000# glass beads; IR 32.3 BPM
Swbd 60 BLO + 112 BFW/24 hrs (-557 BLO)
Squeezed perfs 3488-3584' W/100 sx.
Perf 3344-66', 3400-44' W/1 SPF
Acid (3344-3444') 700 gals.
LOG TOP: San Andres 2640'
After Potential pmpd 54 BO + 6 BW/14 hrs.

