

NM000 - ARTESIA

NM000 - HANDBS

BLM - SANTA RENDRY **NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
New Mexico 0403741B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Atlantic Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T-8-S, R-31-E

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry hole

2. NAME OF OPERATOR
H. L. Brown, Jr.

3. ADDRESS OF OPERATOR
704 Vaughn Building, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
660' FSL & 1980' FWL of Sec. 3, T8S, R31E

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4291.8' GR

12. COUNTY OR PARISH
Chaves
13. STATE
N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☒
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

No productive zones encountered in this well.

On October 13, 1966, we propose to set a 15-sack cement plug at 3920-3726', cut 4-1/2" casing with wireline casing cutter at free point and set a 25-sack cement plug 130' into and 52' above the stub. *(If we shoot casing off below the top of the Yates, we will set a 25-sack cement plug from 1950-2087' and a 25-sack cement plug from 1440-1527'.) We will also set a 25-sack cement plug from 371-287' and a 10-sack cement plug at the surface 31-0'.

All plugs will be set with tubing and the hole filled with 8.9# mud. Well site will then be conditioned for final inspection.

Verbal approval to plug obtained from Mr. Sutherland on October 10, 1966.

*Should we shoot above the base of the anhydrite, then we will set only the stub plug and the plug in and out of the 8-5/8" casing and the surface plug.

18. I hereby certify that the foregoing is true and correct

SIGNED R. Bentley TITLE Agent

DATE Oct. 11, 1966

(This space is for use by State office use)

APPROVED BY OCT 17 1966
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

J. W. SUTHERLAND
DISTRICT ENGINEER

*See Instructions on Reverse Side