

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
New Mexico 0403741B

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Dry hole		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR M. L. Brown, Jr.		8. FARM OR LEASE NAME Atlantic Federal	
3. ADDRESS OF OPERATOR 704 Vaughn Building, Midland, Texas		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1980' FVL of Sec. 3, T8S, R31E		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO.		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 3, T-8-S, R-31-E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4291.8' GR		12. COUNTY OR PARISH Chaves	
		13. STATE N. M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

No productive zones encountered in this well.
On October 13, 1966, we propose to set a 15-sack cement plug at 3920-3726', cut 4-1/2" casing with wireline casing cutter at free point and set a 25-sack cement plug 130' into and 52' above the stub. *(If we shoot casing off below the top of the Yates, we will set a 25-sack cement plug from 1950-2087' and a 25-sack cement plug from 1440-1527'.) We will also set a 25-sack cement plug from 371-287' and a 10-sack cement plug at the surface 31-0'. All plugs will be set with tubing and the hole filled with 8.9# mud. Well site will then be conditioned for final inspection.

Verbal approval to plug obtained from Mr. Sutherland on October 10, 1966.

*Should we shoot above the base of the anhydrite, then we will set only the stub plug and the plug in and out of the 8-5/8" casing and the surface plug.

18. I hereby certify that the foregoing is true and correct

SIGNED R. Busby TITLE Agent DATE Oct. 11, 1966
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.