

COUNTY CHAVES FIELD Chaveros STATE NM

OPR CHAMPLIN PETROLEUM CO. MAP

2 Signal-State

Sec. 1, T-8-S, R-32-E CO-ORD

660' FNL, 1980' FEL of Sec. MC 10494

Spd 8-4-66

Cmp 8-29-66

CSG & SX - TUBING

8 5/8" 360' 250

4 1/2" 4385' 325

LOGS EL GR RA IND HC A

TD 4385', PED 4358'

IP San Andres Perfs 4269-4290' Prpd 22 BOPF + 160 BW. Pct.

Based on 24 hr test, IP 20#, CP 50#, gravity 25.3.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sisson & Norton PROP DEPTH 4500' TYPE

DATE

F.R. 8-4-66

PD 4500' - SA

Contractor - Sisson & Norton

8-8-66 TD 360', WCC.

8-15-66 TD 4152', prep to core.

8-22-66 TD 4385', PED 4358', WO Completion Unit.

Cored 4152-4210', rec 58' anhy dolo., w/scatt
shows oil & wtr.

Cored 4260-4307', rec 47' anhy dolo., w/scatt
shows oil & wtr.

8-29-66 TD 4385', PED 4358', SI for BHP.

Perf @ 4269', 4270', 4271', 4272', 4273',
4274', 4279', 4280', 4281', 4287', 4289',
4290' W/1 SPI

Acid (4269-90') 2000 gals

9-6-66 TD 4385', PED 4358', TC Pump.

9-12-66 TD 4385', PED 4358', TO Pump.

9-19-66

TD 4385', PBD 4358', WO Pot.

Pmpd 22 EO + 160 BW/24 hrs, Gravity 25.3.

9-26-66

TD 4385', PBD 4358', COMPLETE.

LOG TOPS: Yates 2311', Queen 2952',
San Andres 3542'.