

Form 1-66
(May 1966)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved
Budget Bureau No. 43-51404

NMOCC - ARTESIA

NMOCC - HOBBS

BLM - SANTA FE

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
See "APPLICATION FOR PERMIT" for such proposals.

HOBBS

W.F.M.E. Serial #025585

6. IF INDIAN, ALLEGES OR TRIBE NAME

11 42 AM '67

FEB 28

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Ashmun & Hilliard

3. ADDRESS OF OPERATOR
710 Vaughn Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
Unit: "A", 660' from North and East lines

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, OR, etc.)
4142' DF

7. UNIFORMED NAME

8. FARM OR LEASE NAME
Shell Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 3, T 9S, R 30E

12. COUNTY OR PARISH
Chaves

13. STATE
N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACURE TREATMENT	☐	FRACURE TREATMENT	☐
SHOOTING OR ACIDIZING	☐	SHOOTING OR ACIDIZING	☐
REPAIRING WELL	☐	REPAIRING WELL	☐
ALTERING CASING	☐	ALTERING CASING	☐
ABANDON*	☐	ABANDON*	☒
CHANGE PLANS	☐	(Other)	☐

17. PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Commencing October 20, 1966, at 9:00 a.m., operator directed the plugging and abandonment of the above well as follows:

Cement plugs placed:

- 50' 10 sx plug over perforations in 4 1/2" casing from 3245' - 3296'
- 50' 25 sx plug at top of stub of 4 1/2" casing from 1470' - 1520'
- 50' 25 sx plug at bottom of surface of 8 5/8" from 267' - 297'
- 10' 10 sx plug in top of surface pipe

Graveling and wa. applied by pump below, above, and between all plugs.

Pulled 1500' of 4 1/2" casing with pulling tool.

Cemented and worked marker in top of casing.

Plugging operations were completed at 10:30 a.m. on October 21, 1966.

Notification will be given when site is ready to be inspected.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Superintendent

DATE October 28, 1966

(This space for Federal or State use)

TITLE

FEB 27 1967

J. W. Sutherland
DISTRICT ENGINEER

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO