

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

SEP 7 3 21 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-4-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator PAN AMERICAN PETROLEUM CORPORATION	8. Farm or Lease Name QUEEN
3. Address of Operator Box 68, Hobbs, N. M. 88240	9. Well No. 1
4. Location of Well UNIT LETTER C GGO FEET FROM THE NORTH LINE AND 1980 FEET FROM THE WEST LINE, SECTION 10 TOWNSHIP 8-S RANGE 30-E NMPM.	10. Field and Pool, or Wildcat CATO SAN ANDRES
15. Elevation (Show whether DF, RT, GR, etc.)	12. County CHAVES

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER Completion Operations <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

TD 3420, On 8-25-66, 4 1/2" OD 9.5" J-55 Casing was run and set at 3420 w/ 500 s4 12% Gel + 300 s4. Incon neat. Tested casing w/ 2000 psi for 30 minutes. Test OK. After 70 C app 60 hours, app. perforated intervals 3263-65, 73-86, 89-94, 3329-49, 51-61, 68-71 w/ 2 SPS. Acidized w/ 2000 gal. Traced w/ 30,000 gal oil, 40,500" Sand, 3000" glass beads.

On PL. Swab 63 BLO X 72 BNO X 0 BW in 12 hours. GOR 540. Cgr. 25.1°.

TD 3420 + NAY 3763 (San Andres)
PAD 3396 Comp. 9-3-66

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE Area Supr DATE 9-6-66

042-NMOC-11

1- SUSP

APPROVED BY
1- NSW
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____