STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR	I	

OIL CONSERVATION DIVISION

Form C-103 .

SANTA PE	P. O. BOX 2088 Revised 10			
FILE	SANTA FE, NEW MEXICO 87501			
U.S.O.S.		5a. Indicate Type of Lease		
LAND OFFICE		State Fee X		
OPERATOR		5. State Oil & Gas Lease No.		
SUNDR	Y NOTICES AND REPORTS ON WELLS			
(DO NOT USE THIS FORM FOR PAGE	POSALS TO DRILL OR TO DELPEN OR PLUG BACK TO A DIFFERENT RESER ION FOR PERMIT —** (FORM C+101) FOR SUCH PROPOSALS.)	IVOIR.		
1.		7. Unit Agreement Name		
week week	ornem- Water Injection			
2. Name of Operator		8. Farm or Lease Name		
UNION TEXAS PETROLEUM CORPORATION		Baskett		
3. Address of Operator		9. Well No.		
1400 Wilco Bldg., Midland, TX 79701		1		
4. Location of Well		10. Field and Pool, or Wildcat		
K 1	980 FEET FROM THE SOUTH LINE AND 1980	Cato (San Andres)		
	The state of the s			
- West	ON 11 TOWNSHIP 8S HANGE 30E			
THE CINE; SECT.	TOWNSHIP GO HANGE GO			
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County		
	3133' GL	Chaves ()		
16. Chark	Appropriate Box To Indicate Nature of Notice, R	anner or Other Data		
		•		
NOTICE OF IT	ITENTION TO:	JBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING		
TEMPORARILY ASANDON	COMMENCE DRILLING OPH	النبا		
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMEN	T APE T		
	OTHER			
OTHER				
17 Describe Proposed or Completed Or	perations (Clearly state all pertinent details, and give pertinent d	ates, including estimated date of starting any proposed		
work) SEZ RULE 1103.				
Sant 28 1083 -	MIDUSU - Plad wall down managed wallha	ad 0 installed DOD Deleased		
Sept. 28, 1983 - MIRUSU - Bled well down, removed wellhead & installed BOP. Released				
pkr. and POH w/2 3/8" tbg. & pkr. Sept. 29, 1983 - Set CIBP @ 3400' w/35' cement (Class "C") on top. Displaced annulus				
w/10# mud laden gel.				
Sont 20 1002	W/10# mud raden ger.	AEOL DULL 9 mln-o-d 1001		
Sept. 30, 1983 - Placed (40 sx.) 100' cement plug 2350-2450'. PUH & placed 100' cement plug 1050-1150'. Perf. 4 1/2" csg. @ 565' w/4 holes. Set				
	retainer @ 505'. Stung into retainer w/	2 3/8" tbg. & circ. to surt.		
	w/200 sx. Class "C" cement. Placed 10			
	Cut off csg welded on steel plate -	set marker and cleaned up		
	location - <u>WELL NOW P&A</u> .			
		•		
. •				
•				
		. :		
18. I hereby certify that the information	above is true and complete to the best of my knowledge and belie			
	X/			
archeoffeffem Mc	Angigum vive Prod. Services Sur	r. DATE 10-7-83 100 A		
		10N 4 1304 -		
1. 11h	1 State of the same of the sam	STATE OF THE STATE		
APPROVED BY WHATH	WILL & GALL HILL	DATE		
CONDITIONS OF APPROVAL, IF ANY				

RECEIVED

OCT 1 1 1983

O.C.D. HOBBS OFFICE

NA CONTRACTOR