

30-005-10532

COUNTY CHAVES FIELD Cato STATE NM
OPR PAN AMERICAN PETROLEUM CORP. MAP
1 Baskett "F"
Sec. 15, T-8-S, R-30-E
660' ENL, 660' FEI of Sec.
Spd 10-18-66 CO-ORD NO 10532
Cmp 11-8-66 CLASS E
CSG & SX - TUBING
FORMATION DATUM FORMATION DATUM
8 5/8" 460' 300
4 1/2" 3560' 800
LOGS EL GR RA IND HC A
ID 3560', PBD 3530'
IP San Andres Perfs 3414-3524' Pmpd 112 BOPD + 23 BW. Pot.
Based on 24 hr test. Gravity 26., GOR 213.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.
CONT. Cactus Drie. Co. PROP DEPTH 3700' TYPE
DATE

- 10-24-66 D.R. 10-27-66; Opr's Elev. 4118' KB
10-31-66 ED 3500' - SA
Contractor - Cactus
Drlg. 3064'.
11-7-66 ID 3560', PBD 3530', RU Pump.
Perf 3414-21', 3434-50', 3479-3502',
3509-14', 3520-24' W/2 SPF
Acid (3414-3524') 2000 gals.
Swbd 85 BO + 6 BLW/11 hrs
Swbd 56 BO + 3 BW/11 hrs (3414-3524')
11-14-66 ID 3560', PBD 3530', SD Pump Repairs.
Prac (3414-3524') 30,000 gals oil + 30,000# sd.
IR 28.1 BPM
Swbd 168 BLO + 32 BW/12 hrs (3414-3524')
TI 3560', PBD 3530', COMPLETE.
Pmpd 87 BLO, 112 BNO + 23 BW/24 hrs (3414-3524')
LOG TOP: San Andres 2693'.