

100001

COUNTY	CHAVES	FIELD	Cato	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.				MAP
	2	Wasley			
	Sec. 14, T-8-S, R-30-E				CO-ORD
	1980' ENL, 660' FWL of Sec.				MC 10561
	Spd 12-3-66				
	Cup 12-17-66				CLASS
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8" 456' 300					
4 1/2" 3570' 800					
LOGS EL GR RA IND HC A					
TD 3570', PED 3545'					

IP San Andres Perfs 3500-45' Flwd 140 BOPD + 3 BW. Pot. Based on 24 hr test thru 22/64" chk., TP 500#, CP 100#, Gravity 27., GOR 479.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Chico Drlg. Co. PROP DEPTH 3600' TYPE
DATE

F.R. 11-25-66; Opr's Elev. 4119' RE
PD 3600' - SA
Contractor - Chico Drlg. Co.
12-5-66 Drlg. 775'.
12-12-66 Coring @ 3539'.
Cored 3408-60', rec 52' dolo., sli to good
bldg oil, PPP & vert fracs.
Cored 3460-3510', rec 50' being:
41' dns anhy;
9' anhy dolo., bldg oil, PPP, few vert fracs.
12-19-66 TD 3570', PED 3545', COMPLETE.
Cored 3510-60', rec 50' dolo., bldg oil from
PPP & fracs bottom 5'.
Perf 3500-24', 3534-45' W/2 SPF
Acid (3500-45') 3000 gals.
(Holding for tops)
12-27-66 TD 3570', PED 3545', Completion Reported.
LOG TOPS: Yates 1560', Queen 2210', San
Andres 2700'.