STATE NM

COUNTY CHAVES FIELD Cato MAP

OPR PAN AMERICAN PETROLEUM CORP.

CO-ORD

1 Crosby "E" MC 10571 [redacted]

Sec. 10, T-8-S, R-30-E

660' FSL, 660' FWL of Sec.

Spd 12-24-66

Cmp 1-8-67

CLASS			
FORMATION	DATUM	FORMATION	DATUM

CSG & SX - TUBING

8 5/8" 450' 300

4 1/2" 3492' 800

LOGS EL GR RA IND HC A

TD 3492', PBD 3370'

IP San Andres Perfs 3303-52' Flwd 175 BOPD + 1 BLW. Pot. Based on 24 hr test thru 10/64" chk., TP 200#, CP 250#, gravity 26.8, GOR 520.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co. PROP DEPTH 3600' TYPE

DATE

F.R. 12-8-66; Opr's Elev. 4075' KB
PD 3600' - SA
Contractor - Cactus Drlg. Co.

12-19-66 WO Rig.
1-3-67 TD 3492', prep perf.
1-9-67 TD 3492', PBD 3370', COMPLETE.
Perf 3388-3430' W/2 SPF
Acid (3388-3430') 3000 gals; IR 10 BPM
Swbd 3 BO + 362 BFW in 24 hrs (3388-3430')
Set CI Retainer @ 3370'
Squeezed perfs 3388-3430' W/300 sx.
Perf 3303-52' W/2 SPF
Acid (3303-52') 3000 gals + 1500 gals treated Wtr; IR 12.5 BPM
Flwd 43 BO + 11 BLW in 6 hrs thru 20/64" chk., TP 150#, CP 135# (3303-52')
LOG TOPS: Yates 1430', Queen 2085', San Andres 2570'.