

30 005-10572

COUNTY	CHAVES	FIELD	Cato	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.			MAP	
	3	Wasley			
	Sec. 14, T-8-S, R-30-E			CO-ORD	
	560' FNL, 660' FEL of Sec.			MC 10572	
	Spd 12-5-66				
	Cmp 12-22-66				
CSG & SX - TUBING			CLASS		
	FORMATION	DATUM	FORMATION	DATUM	
8 5/8" 458' 300					
4 1/2" 3680' 800					
LOGS EL GR RA IND HC A					
	TD 3680', PBD 3577'				
IP San Andres Perfs 3528-68' Flwd 233 BOPD + 7 BLW. Pot. Based on 24 hr test thru 20/64" chk., TP 125#, CP 625#, Gravity 26.5, GOR 640.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH	3600'	TYPE
DATE			

12-12-66 F.R. 12-8-66; Opr's Elev. 4168' KB
 12-19-66 PD 3600' - SA
 Contractor - Cactus
 Coring @ 3524'.
 TD 3680', PBD 3660', Tstg.
 Cored 3504-34', rec 30' being:
 6' anhy, NS;
 24' dolo., bldg oil, PFP, vert fracs.
 Cored 3534-84', rec 50' being:
 30' dolo., w/PFP, bldg oil & scatt vuggs;
 20' anhy dolo.
 Cored 3584-3634', rec 50' being:
 7' anhy;
 17' dns dolo., w/NS;
 12' dns lm., w/NS;
 9' dolo., bldg oil from vert fracs;
 5' dns lm., bldg oil from frac & PFP 3630-31'.

CHAVES

Cato

NM

Sec. 14-8S-30E

Page #2

FAN AMERICAN PET. CORP., #3 Wasley

19-66 Cont.
Perf 3604-14', 3618-20', 3628-36', 3641-52' W/2 SPF
Acid (3604-52') 3000 gals.
Swbd 160 ELW + 1 RNW/25 hrs (3604-52')
12-27-66 TD 3680', PBD 3577', COMPLETE.
Swbd 33 BW/8 hrs (3604-52')
Set Retainer @ 3580'
Squeezed perfs 3604-52' W/150 sx.
Perf 3528-68' W/2 SPF
Acid (3528-68') 1500 gals.
LOG TOPS: Yates 1650', Queen 2300', San Andres 2780'.