

30005-10574

COUNTY	CHAVES	FIELD	Cato	STATE	NM
OPR	UNION TEXAS PETROLEUM CORP.				MAP
	4 Crosby				
	Sec. 15, T-8-S, R-30-E				CO-ORD
	1980' FNL, 660' FWL of Sec.				MC 10574
	Spd 12-18-66				CLASS
	Cmp 1-13-67				EL
	FORMATION		DATUM		
CSG & SX - TUBING					
8 5/8" 523' 300					
4 1/2" 3533' 300					
LOGS EL GR RA IND HC A					
	TD 3541', PBD 3400'				
IP San Andres Perfs 3360-88' Flwd 102 BOPD. Pot. Based on 24 hr test thru 17/64" chk., TP 150#, Gravity 27.					

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Ard Drlg. Co. PROP DEPTH 3800' TYPE RT
 DATE

F.R. 12-8-66
 PD 3800' - SA
 Contractor - Ard Drlg. Co.
 12-20-66 Drlg. 1220'.
 1-3-67 TD 3541', PBD 3510', WO Comp. Unit.
 1-10-67 TD 3541', PBD 3400', SI Pressure Buildup.
 Perf 3360-88', 3413-33' W/1 SPF
 Acid (3413-33') 2000 gals.
 Swbd 33 B Salt Wtr, w/tr. oil in 15 hrs
 (3413-33')
 Acid (3360-88') 2500 gals.
 Set CIBP @ 3400'
 Swbd 123 BF (98% oil, 2% wtr) in 13 hrs
 (3360-88')
 1-16-67 TD 3541', PBD 3400', WO Potential.
 1-23-67 TD 3541', PBD 3400', COMPLETE.
 LOG TOPS: Anhydrite 1030', Yates 1468',
 San Andres 2683'.

1