

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
OPR	SUNRAY DX OIL COMPANY				
	1 New Mexico State "CG"				MAP
	Sec. 11, T-9-S, R-31-E				CO-ORD
	660' FSL, 660' FWL of Sec.				MC 10576
	Spd 12-6-66				
	Cmp 12-24-66				
	CLASS				
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM	
8 5/8" 379' 250					
4 1/2" 4235' 200					
LOGS EL GR RA IND HC A					
	TD 4250'				
PLUGGED & ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4400'	TYPE
DATE			

F.R. 12-8-66; Opr's Elev. 4355' DF
 PD 4400' - SA
 12-12-66 TD 3980', prep core.
 12-19-66 TD 4250', WOC.
 Cored 3980-4038', rec 58' being:
 6' anhy;
 9' dolo & anhy;
 14' dolo., w/vert fracs;
 4' dolo., w/poor poro., bldg oil;
 25' dolo., w/scatt fracs & PPP, bldg oil.
 Cored 4073-4130', rec 56' being:
 3' dolo., w/NS;
 6' dolo., w/anhy incs;
 1' dolo., w/PPP, bldg oil;
 3' dolo., w/NS;
 1' dolo., w/PPP, bldg oil;
 7' dolo., w/sh strks;
 8' anhy & dolo., w/NS;
 12' dolo., w/NS;

12-19-66

Cont.

1' dolo., bldg oil;
5' dolo., w/sh strks;
1' dolo., w/frac's, bldg oil;
4' dolo., w/any strks;
4' dolo., w/NS.
Perf @ 4083', 4094', 4103', 4113', 4117',
4128' W/1 SPI

Acid (4083-4128') 750 gals.

Swbd 22 B Salt Wtr in 3 hrs (4083-4128')

Squeezed perfs 4083-4128' W/100 sx.

12-27-66

TD 4250', PBD 4049', PLUGGED & ABANDONED.

Perf @ 4053', 4064', 4068' W/1 SPI

Swbd 9 B Salt Wtr in 3 hrs (4053-68')

Squeezed perfs 4053-68' W/100 sx.

Perf @ 4010', 4013', 4016', 4035', 4038',
4041' W/1 SPI

Acid (4010-4041') 1000 gals.

Swbd 24 BAW + 16 BLO in 2 hrs (4010-4041')

LOG TOPS: Anhydrite 1535', Yates 2055',

Queen 2850', San Andres 3272'.