

COUNTY CHAVES FIELD Chaveroo STATE NM OWWO
 OPR ADOBE OIL CO. MAP
1 Chaves-State
Sec. 1, T-8-S, R-32-E CO-ORD
1980' FNL, 1980' FEL of Sec. MC 10582

		CLASS		EL	
Re-Cmp 1-17-68		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8"	380'	250			
4 1/2"	4340'	200			
LOGS EL GR RA IND HC A					
		TD 4340', PBD 4304'			

San Andres Perfs 4171-4287' - NO NEW POTENTIAL

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH TYPE WO
 DATE

2-12-68 F.R.C. 2-15-68; OWWO
 (Orig Cmp 1-27-67 from SA Perfs 4259-84',
 OTD 4340', OPB 4304')
 TD 4340', PBD 4304', COMPLETE
 Perf @ 4171', 4192', 4207', 4218' W/2 SPI
 Perf @ 4176', 4184', 4198' W/1 SPI
 Acid (4171-4218') 1000 gals.
 Frac (4171-4218') 24,000 gals oil + 30,000# ad.
 Pmpd 71 BNO + 35 BW in 24 hrs, GOR 1549,
 Gravity 24.6 (4171-4287')

CHAVES Chaveroo NM
ADOBE OIL CO., #1 Chaves-State

Sec. 1-8S-32E
Page #2

1-30-67 TD 4340', PBD 4304', tstg on pump.
Pmpd 60 BO in 24 hrs.
2-6-67 TD 4340', PBD 4304', WO Pot.
Pmpd 58 BO + 10 BW in 24 hrs, GOR 1431,
Gravity 24.7.
2-13-67 TD 4340', PBD 4304', COMPLETE.
LOG TOPS: Anhydrite 1880', B/Salt 2200',
Yates 2300', Queen 2970', Grayburg 3480',
San Andres 3540'.

30-005-10582

COUNTY	CHAVES	FIELD Chaveroo	STATE NM
OPR	ADOBE OIL COMPANY		MAP
1 Chaves-State			
Sec. 1, T-8-S, R-32-E		CO-ORD	
1980' FNL, 1980' FEL of Sec.		MC 10582	
Spd 12-20-66		CLASS	
Cmp 1-27-67	FORMATION	DATUM	FORMATION
CSG & SX - TUBING			
8 5/8" 380' 250			
4 1/2" 4340' 200			
LOGS EL GR RA IND HC A			
TD 4340', PBD 4304'			

IP San Andres Perfs 4259-4287' Pmpd 58 BOPD + 10 BW. Pot. Based on 24 hr test, gravity 24.7, GOR 1431.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton PROP DEPTH 4500' TYPE RT
DATE

F.R. 12-15-66
PD 4500' - SA
Contr. - Sitton & Norton
12-30-66 TD 4340', running casing.
1-9-67 TD 4340', PBD 4304', WO Electricity.
Perf @ 4259', 4264', 4265', 4273', 4275',
4277', 4282', 4284', 4287' W/1 SPI
Acid (4259-87') 1000 gals.
Swbd dry (4259-87')
Acid (4259-87') 4000 gals.
Frac (4259-87') 30,000 gals oil + 45,000# sd.
1-16-67 TD 4340', PBD 4304', WO Electricity.
1-23-67 TD 4340', PBD 4304', WO Electricity.