

N. M. OIL CONS. COMMISSION  
P. O. BOX 1860  
HOBBS, NEW MEXICO 88240  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Kelt Oil & Gas, Inc.

3. Address and Telephone No.

P.O. Box 779 - Goldsmith, TX 79741 (915) 827-3818

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FEL NWSE Sec. 14-T8S-R30E

Unit J

5. Lease Designation and Serial No.

NMNM82050X (NM-0444628)

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cato Unit #112

9. API Well No.

30-005-20016

10. Field and Pool, or Exploratory Area

Cato San Andres

11. County or Parish, State

Chavez, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

PROPOSED OPERATIONS: (All measurements refer to KB)

- 1) Set CIBP @ 3400'
- 2) Dump 4 sx cmt on top of CIBP.
- 3) Turn hole over to mud. (50 bls)
- 4) Lay in cmt plug f/1500' - 1400'. (8sx)
- 5) Lay in cmt plug f/520' - 420'. (7 sx)
- 6) Lay in cmt plug f/50' - Surf. (4 sx)

DATA:

8 5/8" - 24# csg f/0' - 470'; cmt circulated; 11" bit.  
4 1/2" - 9.5# csg f/0' - 3660'; cmt circulated; 7 7/8" bit. (800 sx cmt)  
TD = 3660' PBTD = 3570' Perfs f/3497' - 3544'



14. I hereby certify that the foregoing is true and correct

Signed Matthew C. Detwain

Title Petroleum Engineer


Date March 8, 1994

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:



Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side