

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.NMDC - ARTESIA
NMDC - HOBBS
BLM - SANTA FE

SUMMARY NOTICES AND REPORTS ON WELLS

HOBBS OF

5. LEASE DESIGNATION AND SERIAL NO.

NM-0444628

6. NAME AND ADDRESS OF ALLOTTEE OR TRIBE NAME

C.E.C.C.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CATO "C" Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

CATO San Amares

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

14-8-30 NMPM

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any G.S. Survey
See also space 17 below.)
At surface

ROSWELL, NEW MEXICO

1980 FSL x 1980 FEL, Sec. 14 (Unit J, NW 1/4 SE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

4158 R.D.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

On 1-31-67, 4 1/2" OD 9.5" J-55 Casing was set @ 3660 (TD) w/ 500 sy.
12% Gel + 300 sy. neat Incon. Tested casing w/ 2200
psi for 30 minutes. Test O.K. Perforated 3580-3628 w/ 25 PF.
Acidized w/ 3000 gal 28%. Evaluated. Dry. Set CI Retainer @
3570 and squeezed plugs 3580-3628 w/ 150 sy. cement. Perforated
3497-3544 w/ 215 PF. Acidized w/ 3000 gal 28%. Evaluated.

On PT. Flow. 206 BOP O BW in 24 hours thru 29/64 Choke. TPF-200.
CDF-60. GOR 408, BAMCFG, 25.9° API gravity.

TD - 3660

comp. 2-5-67

PBD - 3570

TAPY - 3497 - San An L

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AREA SUPERINTENDENT

DATE

2-7-67

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

04- USGS - ROS
1- NSW
1- SUSP
1- RRY

*See Instructions on Reverse Side

