Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

NMOCC - ARTESIA
NMOCC - HOBBS
BLM - SANTA FE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

MAR 15 11 45 AM '67

5. LEASE DESIGNATION AND SERIAL NO.: NM-0142233

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

1. OIL WELL [X] GAS WELL [ ] OTHER

8. FARM OR LEASE NAME: CROSBY "A" Federal

2. NAME OF OPERATOR: PAN AMERICAN PETROLEUM CORPORATION

9. WELL NO.: 1

3. ADDRESS OF OPERATOR: BOX 68, HOBBS, N. M. 88240

10. FIELD AND POOL, OR WILDCAT: CATO San Andres

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: 8-8-30 NMPM

660'FSL x 660'FEL Sec. 8, (Unit P, SE/4 SE/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 4064' R.D.B.

12. COUNTY OR PARISH: Chaves

13. STATE: N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[X]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other) Completion			[X]
(Other)			[ ]	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 2-26-67 4½" OD 9.5# J-55 Casing was set @ 3414 (TD) w/ 500 sx 12% Gel + 300 sx Incor Neat. Tested casing w/ 2000 psi for 30 minutes. Test O.K. Perforated interval 3308-47 w/2SPF. Acidized w/5000 gal 28%. Evaluated. Perforated intervals 3158-3200, & 3232-68 w/2SPF. Acidized w/ 5000 gal 28%. Evaluated

On PT- 9 BW 124 BO x 20 BLW in 24 hours thru 12/64" Choke. TPF 500 CPF 526 GOR 1400 174 MCFG.

TD-3414'
PBD - 3367'
TAY - 3158 - San Andres.
Comp - 3-8-67

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE AREA SUPERINTENDENT DATE 3-9-67

(This space for Federal or State office use)

APPROVED BY _____ TITLE ACCEPTED FOR RECORD J. W. Sutherland District Engineer DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

O+4- USGS - ROSWELL
1- NSW
1- SUSP
1- RRY