

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
OG 1063	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator JACK L. McCLELLAN		8. Farm or Lease Name KLEPFER STATE
3. Address of Operator Box 848, ROSWELL, NEW MEXICO 88201		9. Well No. 1
4. Location of Well UNIT <u>D</u> <u>330</u> FEET FROM THE <u>NORTH</u> LINE AND <u>330</u> FEET FROM <u>WEST</u> LINE, SECTION <u>12</u> TOWNSHIP <u>8-S</u> RANGE <u>33-E</u> NMPM.		10. Field and Pool, or Wildcat CHAUEROO
15. Elevation (Show whether DF, RT, GR, etc.) 4346' G. L.		12. County CHAVES

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PURSUANT TO VERBAL APPROVAL BY J. W. RUNYAN ON FEBRUARY 17, 1969, THIS WELL WILL BE PLUGGED AND ABANDONED AS FOLLOWS: 25 SX CEMENT PLUG AT 4382', 25 SX PLUG IN AND OUT OF 4 1/2" CASING STUB AT APPROXIMATELY 3500', 25 SX PLUG AT 2350' (BASE OF SALT), 25 SX PLUG AT 1956' (TOP OF SALT), 25 SX PLUG IN AND OUT OF 8-5/8" CASING AT 402', 10 SX PLUG AT SURFACE WITH MARKER. HEAVY MUD WILL BE PLACED BETWEEN ALL PLUGS. ESTIMATED TOP OF CEMENT BY TEMP. SURVEY 3550'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Jack L. McClellan</u>	TITLE <u>OPERATOR</u>	DATE <u>2/17/69</u>
APPROVED BY <u>John W. Runyan</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		