

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP STATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

NM0000 - MINNEAPOLIS

NM0000 - MINNEAPOLIS

BLM - SANTA FE

SUNDARY NOTICES AND REPORTS ON WELLS

HUBBS OFFICE O. C. C.

MAR 9 11 31 AM '67

5. LEASE DESIGNATION AND SERIAL NO.

NM0142233

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Baxter-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Cato (San Andres)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

17-T-8-S, R-30-E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR

1300 Wilco Bldg., Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FN & WL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4116' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud at 5:00 PM 2-15-67

2-16-67 TD 518' Set 8-5/8" OD 20# new casing at 514' and cemented w/300 sx Incor by BJ precess. Cement circulated. WOC 24 hrs. Tested 8-5/8 casing to 1000# for 30 minutes. Tested OK.

Reached TD of 3450' on 2-21-67

2-22-67 TD 3450' Set 4 1/2" OD 9.5# new casing at 3448' and cemented w/150 sx. Incor cmt. 12% Gel 1/4# Flocele and 5# Gilsonite per sk. and 150 sx. 50-50 Posmix 2% Gel and 10# salt per sack by BJ process. Top of cmt. outside of 4 1/2" OD casing at 2360' by TS. WOC 24 hrs. and tested 4 1/2" OD casing to 1000# for 30 minutes. Tested OK.

RECEIVED

MAR 8 1967

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Office Supervisor

DATE 3-6-67

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

District Engineer