

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.				MAP
1 Miller-Federal					
Sec. 34, T-7-S, R-31-E				CO-ORD	
660' FSL, 660' FEL of Sec.				30-005-20044	
Spd 3-15-67					
Cmp 4-13-67					
		CLASS		EL	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8"	465'	300			
4 1/2"	4385'	800			
LOGS EL GR RA IND HC A					
		TD 4385'; PBD 4025'			

IP San Andres Perfs 3954-84' Pmpd 57 BOPD + 38 BW. Pot. Based on 24 hr test; gravity 26.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co. PROP DEPTH 4500' TYPE RT
DATE

F.R. 3-16-67; Opr's Elev. 4325' KB
PD 4500' - SA
Contr. - Cactus
3-20-67 Drlg. 3364'.
3-27-67 TD 4385', prep run casing.
4-3-67 TD 4385', PBD 4200', prep swab.
Perf 4299-4300', 4306-08', 4314-16' W/2 SPF
Acid (4299-4316') 1000 gals.
Swbd & Flwd 68 BLW in 15 hrs & swbd dry (-32 BLW)
Perf 4054-58', 4063-65', 4069-70', 4104-06',
4136-38', 4141-43', 4146-48' W/2 SPF
Set BP @ 4200'
Acid (4054-4148') 3000 gals.
Swbd 73 BLW, w/tr. oil in 6 hrs (4054-4148')
Frac (4054-4148') 20,000 gals oil + 20,000# sd.

CHAVES Wildcat NM
PAN AMERICAN PET. CORP., #1 Miller-Federal

Sec. 34-7S-31E
Page #2

4-10-67

TD 4385', PED 4025', prep to TOP
Swbd 39 BLO + 13 BLW + 14 BFWPD (4054-4148')
Perf 3954-84' W/2 SPF
Set BP @ 4025'
Acid (3954-84') 3000 gals.
Swbd 80 BO + 51 BFW in 24 hrs. (3954-84')
Swbd 5 BFPH (25% wtr)
4-17-67 TD 4385', PBD 4025', COMPLETE.
LOG TOPS: San Andres 3120', Pil Zone 3669'.