

NO. OF COPIES REQUIRED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- TA	7. Unit Agreement Name
2. Name of Operator Union Texas Petroleum Corporation	8. Farm or Lease Name Crosby
3. Address of Operator 1300 Wilco Building, Midland, Texas 79701	9. Well No. 12
4. Location of Well UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 8-S RANGE 30-E NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, CR, etc.) 4120' DF	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

- 8-5/8" surface csg set at 534'; cemented with 300 sx cement and circulated.
- 4-1/2" production casing set at 3599' cemented with 300 sx, top cement 2230'.
- Csg. perforations 3339-3370' (31 holes) 1 shot per foot, and 3409-3421 (12 holes) 1 shot per foot.
- Spot cement plug from 3421-3000' using 35 sx cement.
- Spot cement plug from 2243-2043', using 50 sx cement. (Cut and pulled 2143' of 4 1/2" Csg.)
- Spot 100' cement plug from 920-1020' using 40 sx cement
- Spot cement plug 100' below and 100' in 8-5/8" csg, 634-434', using 75 sx cement.
- Spot 10 sx cement plug 30' to surface
- Weld on 1/2" steel plate on 8-5/8" casing.
- Install dry hole marker in accordance with regulations.

NOTE: Mud laden fluid of 10# gal. left in well

Well plugged and abandoned 10/18/72

The pits and location have been leveled and cleared of all junk.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert T. Plummer TITLE Operations Supt.-Western DATE 12-19-72

APPROVED BY Nathaniel E. Clegg TITLE OIL & GAS DATE 12-19-72

BONANZA CASING PULLERS, INC.

PHONE 505 397-3263 P. O. Box 2445
HOBBS, NEW MEXICO 88240

PLUGGING RECORD

OPERATOR Union Texas Petroleum
LEASE Crosby WELL# 12
COUNTY Chaves STATE N. M. LEGAL DESCRIPTION _____

PLUG NO.	SACKS	DEPTH OF PLUG TO BOTTOM-TOP	REMARKS
1	35	3421-3000	
2	50	2243-2043	4½" Stub
3	40	1020- 420	
4	75	634- 434	
5	10	Surface	

I certify that the placing of cement plugs as shown on this report was performed by me or under my supervision and that the cementing data presented are correct and complete to the best of my knowledge.

This certification covers cementing data only.

Distribution: 2-Operator
1-File

Signature Allen D. Jernod
Title President

RECEIVED

1 2 1972

OIL CONSERVATION COMM.
HOELS, H. M.