

COUNTY	CHAVES	FIELD	Cato	STATE	NM
OPR	PAN AMERICAN PETROLEUM CORP.				MAP
	2 Cato "A" Federal				
	Sec. 15, T-8-S, R-30-E				CO-ORD
	1980' FSL, 660' FWL of Sec.				30-005-20056
	Spd 4-2-67				CLASS
	Cmp 4-15-67				EL
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM	
8 5/8" 455' 300					
4 1/2" 3555' 600					
LOGS EL GR RA IND HC A					
	TD 3555'; PBD 3520';				

IP San Andres Perfs 3386-3515' Swbd 110 BOPD + 49 BW. Pot.
Based on 24 hr test, gravity 24.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus	PROP DEPTH	3600'	TYPE	RT
DATE				

F.R. 4-6-67; Opr's Elev. 4146' KB
PD 3600' - SA
Contractor - Cactus
4-3-67 TD 455', WOC.
4-10-67 TD 3555', MO Rotary.
4-17-67 TD 3555', PBD 3520', COMPLETE.
Perf 3480-3515' W/2 SPF
Acid (3480-3515') 3000 gals + 1500 gals treated
wtr
Swbd 25 BO + 155 BLW in 15 hrs.
Swbd 9 BO + 18 BFW in 10 hrs. (3480-3515')
Perf 3386-3446' W/2 SPF
Acid (3386-3446') 5000 gals.
Swbd 110 BO + 23 BLW + 49 BFW in 24 hrs
(3386-3515')
(Holding for tops)

CHAVES Cato NM Sec. 15-8S-30E
PAN AMERICAN PET. CORP., #2 Cato "A" Federal Page #2

4-24-67

TD 3555', PBD 3520', Completion Reported.
LOG TOPS: Yates 1550', Queen 2235', San
Andres 2698'.