

COUNTY	CHAVES	FIELD	Wildcat	STATE	NM
OPR	CACTUS DRILG. CORP. OF TEXAS				
	1 Schuman				
	Sec. 29, T-7-S, R-31-E				
	1980' FNL, 660' FWL of Sec.			CO-ORD	
	Spd 5-9-67			30-005-20070	
	Cmp 6-15-67			CLASS	
				ED	
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM	
8 5/8" 358' 175					
4 1/2" 4000' 200					
LOGS EL GR RA IND HC A					
	TD 4000'				
PLUGGED & ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. B&L Drilg. Co. PROP DEPTH 4100' TYPE RT
DATE

5-15-67 F.R. 5-11-67; Opr's Elev. 4312' KB
5-22-67 PD 4100' - SA
Contr. - B&L Drilg. Co.
Drilg. 3415'.
5-29-67 TD 4000', prep Acid.
Perf 3747-57', 3764-79' W/1 SPF
Acid (3747-79') 1000 gals (MA)
Swbd dry, w/sli show oil (3747-79')
5-29-67 TD 4000', PKD 3730', SI.
Acid (3747-79') 5000 gals.
Swbd 1 BLWPH (6% new oil) (-140 BLW)
Set BP @ 3730'
Perf @ 3642', 3649', 3656', 3668', 3673',
3677', 3680', 3683', 3686', 3692' W/1 SPI
Acid (3642-92') 2000 gals 15%
Swbd load
Swbd @ rate of 1 1/2 BFWPH w/tr oil (3642-92')

CHAVES Wildcat NM
CACTUS DRILG. CORP. OF TEXAS, #1 Schuman

Sec. 29-7S-31E
Page #2

6-5-67 TD 4000', PBD 3630', prep to P&A.
Set BP @ 3630'
Perf @ 3584', 3589', 3595', 3599', 3600',
3601', 3606', 3610', 3611', 3612', 3613',
3614' w/1 SPI
Acid (3584-3614') 2000 gals.
Swbd 1½ BAWPH & swbd dry
Did not rec load (3584-3614')
6-12-67 TD 4000', PBD 3630', prep to P&A.
6-19-67 TD 4000', PBD 3630', PLUGGED & ABANDONED.
LOG TOPS: San Andres 2895', Pi Marker
3408'.