

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 19 3 07 PM '67

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name CROSBY "D"
9. Well No. 2
10. Field and Pool, or Wildcat CATO San Anas
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator PAN AMERICAN PETROLEUM CORPORATION
3. Address of Operator BOX 68, HOBBS, N. M. 88240
4. Location of Well UNIT LETTER <u>F</u> , <u>1980</u> FEET FROM THE <u>NORTH</u> LINE AND <u>1980</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>15</u> TOWNSHIP <u>8-S</u> RANGE <u>30-E</u> N.M.P.M.
15. Elevation (Show whether DP, RT, GR, etc.) 4090 R.D.B.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <u>Completion</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 7-12-67, 4 1/2" OD 9.5# J-55 Casing was set @ 3531 w/300 psi. Incar. Tested casing w/ 2000 psi for 30 minutes. WOC appx. 60 hours.

Perforated intervals 3364-69, 3394-3405, 30-46, 55-80 w/25PF. Acidized w/ 4000 gal 28%. Evaluated.

PT-7-15-67. Flowed 153 BO x 10 BLW in 24 hours thru 18/64" ch. TPF-100, CPF-700. Cgr. 26°. GOR 640, 98 MCFG.

TD-3531

PAD-3511

TPAY 3364 San And.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Adm. Super. DATE 7-19-67

012-NMOC-11

1-NSW

1-SUSP

1-R124

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE