DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reserveir. Use form 9-331-C for such proposals.) 1. oil ### 235	Form 9-331 Dec. 1973 HOBBS, NEW MEXICO 88240	Budget Bureau No. 42-R1424
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to despen or plug back to a different reservoir. Use form -311-Cfor use here proposals to drill or to despen or plug back to a different reservoir. Use form -311-Cfor use here proposals to drill or to despen or plug back to a different reservoir. Use form -311-Cfor use here proposals to drill or to despen or plug back to a different reservoir. Use form -311-Cfor use here proposals to drill or to despen or plug back to a different reservoir. Use form -311-Cfor use here proposals to drill or to despen or plug back to a different reservoir. Use form -311-Cfor use here proposals to drill or to despen or plug back to a different reservoir. 8. FARM OR LEASE NAME MILITOR FEED OF REAL REPORT OF The Section of the MILITOR OF THE DOT OF NOTICE. REPORT, OR OTHER DATA 12. COUNTY OR PARISH I3. STATE Chaves NAME AND WELL REPORT OF THE DOT OF THE	UNITED STATES	
SUNDRY NOTICES AND REPORTS ON WELLS Co not use this form for proposals to drill or to despen or plug back to a different secretic the free-proposals. 1. oil Fit @ss	DEPARTMENT OF THE INTERIOR	
SUNDRY NOTICES AND REPURS ON WELLING 1. oil well	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPURS ON WELLING 1. oil well		7 UNIT ACDEEMENT NAME
1. oil Se see See See See See See See See See	SUNDRY NOTICES AND REPORTS ON WELLS	7. ONL AGREEMENT NAME
1. oil well A gas well other 2. NAME OPERATOR 3. WELL NO. 2. NAME OPERATOR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1. SEC., T., R. M., OR BLK. AND SURVEY OR AREA NWSE Sec. 34: T7S, R31E 12. COUNTY OR PARISH 13. STATE Chaves New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KD8, AND WD) 4326' RDB REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KD8, AND WD) 4326' RDB 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated depths for all markers and zones pertinent to this work.) 18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated depths for all markers and zones pertinent to this work.) 18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated depths for all markers and zones pertinent to this work.) 18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated depths for all markers and zones pertinent to this work.) 18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and m	(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	B. FARM OR LEASE NAME
2 NAME OF OPERATOR Haseloff Corporation 3. ADDRESS OF OPERATOR Dox 249, Lovington, NM 88260 4. Location of Well (Report Location Clearly See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)' 01-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates Formation from 2100' back to 2900'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type 10. FIFLD OR WILLDCAT NAME Tom Tom—San Andres 11. SEC. T. M., OR BLK. AND SURVEY OR AREA TOM, TOM-SURVEY OR AREA TOM Tom—San Andres 11. SEC. T. M., OR BLK. AND SURVEY OR AREA TOM, TOM-SURVEY OR AREA TOM Tom—San Andres 11. SEC. T. M., OR BLK. AND SURVEY OR AREA TOM, TOM-SURVEY OR AREA TOM Tom—San Andres 11. SEC. T. M., OR BLK. AND SURVEY OR AREA TOM, TOM-SURVEY OR AREA TOM Tom—San Andres 11. SEC. T. M., OR BLK. M., OR BLK. AND SURVEY OR AREA TOM Tom—San Andres 11. SEC. T. M., OR BLK. AND SURVEY OR AREA TOM, TOM-Survey OR AREA TOM		
Haseloff Corporation 3. ADDRESS OF OPERATOR 1. Box 249, Lovington, NM 88260 4. LCCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FSL 1980' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALITER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true wertical depths for all markers and zones pertinent to this work.)' 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true wertical depths for all markers and zones pertinent to this work.)' 18. ELEVATIONS (SHOW DF, KDB, AND WD) 4326' RDB 19. ELEVATIONS (SHOW DF, KDB, AND WD) 4326' RDB (NOTE: Report results of multiple completion or zone form 9-330.) (NOTE: Report results of multiple completion or zone form 9-330.) (NOTE: Report results of multiple completion or zone form 9-330.) 19. ELEVATIONS (SHOW DF, KDB, AND WD) 4326' RDB (NOTE: Report results of multiple completion or zone form 9-330.) (NOTE: Report results of multiple completion or zone form 9-330.) 19. ELEVATIONS (SHOW DF, KDB, AND WD) 4326' RDB (NOTE: Report results of multiple completion or zone form 9-330.) 19. ELEVATIONS (SHOW DF, KDB, AND WD) 4326' RDB (NOTE: Report results of multiple completion or zone form 9-330.)		- · · · - · · · · · · · · · · · · · · ·
3. ADDRESS OF OFERATOR P. Box 249, Lovington, NM 88260 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FSL 1980' FEL AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOT ON ALIDIZE REPAIR WELL HOTEL COMPLETE CHANGE ZONES 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. ELEVATIONS (BHOW DF, KDB, AND DE ARCA, NNSE Sec. 34: T75, R31E 19. ELEVATIONS (BHOW DF, KDB, AND DE ARCA, NNSE Sec. 34: T75, R31E 10. API NO. 15. ELEVATIONS (BHOW DF, KDB, AND DE ARCA, NNSE Sec. 34: T75, R31E 10. API NO. 16. COUNTY OF PARISH 18. API NO. 16. API NO. 16. COUNTY OF PARISH 18. API NO. 16. CHECK APPROVAL TO, SEC. 18. API NO. 19. A	2. NAME OF OPERATOR Lynn fet Consu	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 4. SUBSEQUENT SEL 1980 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900 to 3980 to 90 f plug at 3850 . 2) Set 100 cement plug across shoe 50 in 50 out, 395 back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50 cement plug at surface. 5) Installed P & A marker. Subsurface Safety Valve: Manu. and Type Fig. 2. County OR PARISH 13. STATE (Chaves National Parish Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 16. CHECK APPROPARISH 13. STATE (Chaves New Mexico 14. API NO. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates (Chaves New Mexico 14. API NO. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent	Haseloff-Corporation /	10. FIFLD OR WILDEN! NAME
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FSL 1980' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	3. ADDRESS OF OPERATOR Toxington NM 88260	
AL COCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below). AT SURFACE: 1980' FSL 1980' FEL 12 COUNTY OR PARISH 13. STATE Chaves AT TOP PROD. INTERVAL: AT TOP AT DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHAPRE SHUT-OFF CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 01-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.		, · · · · · · · · · · · · · · · · · · ·
AT SURFACE: 1900' FEL 1900' FEL 1900' FEL AT TOP PROB. INTERVAL: API NO. 14. API NO. 15. ELEVATIONS (\$HOW DF, KDB, AND WD) 4326' RDB (NOTE: Report results of multiple completion or zone change on Form 9-330.) (NOTE: Report results of multiple completion or zone change on Form 9-330.) (NOTE: Report results of multiple completion or zone change on Form 9-330.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yâtes formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.		
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates Formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.	1000 651 1000 661	12. COUNTY OR PARISH 13. STATE
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	AT TOP PROD. INTERVAL:	Chaves New Mexico
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900 to 3980 top of plug at 3850 . 2) Set 100 cement plug across Yates formation from 2100 back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50 cement plug at surface. 5) Installed P & A marker.		14. API NO.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING WILTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.		
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES RABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.	REPORT, OR OTHER DATA	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4)20 RDB
SHOOT OR ACIDIZE REPAIR WELL CHAPPER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 01-22-86 1) Set cement plug across perf's 3900 to 3980 top of plug at 3850 . 2) Set 100 cement plug across Yates formation from 2100 back to 2000 . 3) Set cement plug across shoe 50 in 50 out, 395 back to 295 Plug set in and behind the 4 1/2 casing. 4) Set 50 cement plug at surface. 5) Installed P & A marker.		;
REPAIR WELL PULL OR ALTER CASING		· · ·
PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* O1-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.		(NOTE: Report results of multiple completion or zone
CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* O1-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.		
ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* O1-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.	MULTIPLE COMPLETE	# 2
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 101-22-86 1) Set cement plug across perf's 3900 to 3980 to open of plug at 3850 to open plug at 3850 to open plug across Yates formation from 2100 to back to 2000 to open plug across shoe 50 to out, 395 back to 295 Plug set in and behind the 4 1/2" casing. 4) Set 50 cement plug at surface. 5) Installed P & A marker.	·····-	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* O1-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.		14
including estimated date of starting any proposed work. If well is directionally direct, we substitute measured and true vertical depths for all markers and zones pertinent to this work.)* O1-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker. Subsurface Safety Valve: Manu. and Type	·	41-4
o1-22-86 1) Set cement plug across perf's 3900' to 3980' top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker.	including actimated data of starting any proposed work. If well is (ditectiously dimed kide supstitute receivers and
top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker. Set @F	measured and true vertical depths for all markers and zones pertine	nt to this work.)*
top of plug at 3850'. 2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker. Set @F	01-22-86 1) Set cement plug across	perf's 3900 to 3980
2) Set 100' cement plug across Yates formation from 2100'' back to 2000'. 3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker. Set @	top of plug at 3850'.	Poll 2 3,00; or 3,00
3) Set cement plug across shoe 50' in 50' out, 395' back to 295'. Plug set in and behind the 4 1/2" casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker. Set @F	2) Set 100° cement plug a	cross Yates Formation from
back to 295°. Plug set in and behind the 4 1/2" casing. 4) Set 50° cement plug at surface. 5) Installed P & A marker. Subsurface Safety Valve: Manu. and Type		
casing. 4) Set 50' cement plug at surface. 5) Installed P & A marker. Subsurface Safety Valve: Manu. and Type		
4) Set 50' cement plug at surface. 5) Installed P & A marker. Subsurface Safety Valve: Manu. and Type		in and benind the 4 1/2
5) Installed P & A marker. Subsurface Safety Valve: Manu. and Type		surface.
	A O-f-h-Mohan Manu and Tuno	Set @ F
18. I hereby certify that the foregoing is true and correct	Subsurface Safety Valve: Manu. and Type	i
	18. I hereby certify that the foregoing is true and correct	

TITLE APPROVED DATE PETER W. CHESTER DATE Approved as to plugging of the well bore. FEB £ 1987

Liability under bond is retained until surface restoration is completed.

BUREAU THAT MARAGEMENT - ROSWELL RESOURCE AREA