

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI
(Other instruction
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0174830-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Adam K. Grafe Associates, Inc. & The Wil-Mc Oil Corp.		8. FARM OR LEASE NAME Atlantic-Richfield	
3. ADDRESS OF OPERATOR 3900 Lemmon Avenue, Dallas, Texas 75219		9. WELL NO. Federal 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FEL 1980' FSL, Sec. 8, T8S, R33E Chaves County, New Mexico		10. FIELD AND POOL, OR WILDCAT Chaveroo	
14. PERMIT NO.		11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA Sec. 8, T8S, R33E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4423 G		12. COUNTY OR PARISH Chaves	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Surface Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Spud 3:30 p.m. 7-30-67.
2. Drilled 12 $\frac{1}{4}$ " hole to 350'.
3. Set 8-5/8" casing at 340'.
4. Cemented with 250 sacks regular cement with 2% gel. Circulated cement.
5. Tested casing to 1000 psi before drilling plug. Held O.K. for 30 minutes.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Vice President

DATE

8-10-67

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

AUG 11 1967

*See Instructions on Reverse Side

J L GORDON
ACTING DISTRICT ENGINEER