

NM0000 - ARTESIA
NM0000 - HODGES
BLM - SANTA FEUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICAT.

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESERVOIR ☐

2. NAME OF OPERATOR

Shell Oil Company (Western Division)

3. ADDRESS OF OPERATOR

P. O. Box 1509, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1980' FSL and 1980' FWL, Sec. 23, T-8-S, R-30-E,
NMPM Survey, Chaves County, New Mexico

At top prod. interval reported below

same

At total depth

same

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

8-14-67

16. DATE T.D. REACHED

8-22-67

17. DATE COMPL. (Ready to prod.)

8-24-67

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

4209'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

3710'

21. PLUG, BACK T.D., MD & TVD

3676'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-3710'

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

3562', 3566', 3572', 3576', 3578', 3582', 3583', 3585', 3591',
3595', & 3598'. San Andres25. WAS DIRECTIONAL
SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

SNP, FDC, LL & MLL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	53.5#	460'	12 1/4"	250 sacks	-
4 1/2"	10.5#	3710'	7 7/8"	400 sacks	-

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2"	3456'	3456'

31. PERFORATION RECORD (Interval, size and number)

3562', 3566', 3572', 3576', 3578', 3582',
3583', 3585', 3591', 3595', & 3598'.

(11 holes)

1-1/2" JS

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3710'	125 gals. 15X
	4000 gals. 28X + 5 gal/1000
	AS-5, 3 gal/1000 14-M, 2 gal/1000
	HAI-50 & 5#/1000 gals. FR-10

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
8-24-67		Flowing					Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
8-27-67	4	26/64"	→	67	38	3	567	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
170 psi	-	→	408	228	3	24.7° api		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

Logs and Deviation Record

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

Original Signed By

SIGNED J. D. Duren TITLE Staff Petrophysical Engineer DATE August 28, 1967

*(See Instructions and Spaces for Additional Data on Reverse Side)

ACCEPTED FOR RECORD

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
San Andres	3558'	3600'	Hydrocarbon bearing Water and hydrocarbon bearing Water and hydrocarbon bearing	Base Red Beds Yates San Andres San Andres Marker Slaughter A Zone Slaughter B-C Zone	1130'	(+3079')
	3627'	3639'			1672'	(+2537')
	3660'	3670'			2835'	(+1371')
					3389'	(+ 820')
					3542'	(+ 667')
					3627'	(+ 582')

NEW MEXICO OIL COMMISSION

OPERATOR SHELL OIL COMPANY ADDRESS P. O. Box 1509, Amarillo, Texas
FIELD Chaves LEASE Hodges Federal #3 WELL NO. 3
LOCATION 1980' FSL & 1980' FWL, Sec. 23, T-8-S, R-30-E, Chaves County, New Mexico

DEVIATION RECORD


<u>Depth (feet)</u>	<u>Angle of Inclination (degrees)</u>	<u>Displacement (feet)</u>	<u>Accumulative Displacement (feet)</u>
460	1/2	3.74	3.74
937	3/4	6.25	9.99
1,437	3/4	6.55	16.54
1,937	1	8.75	25.29
2,302	1	6.38	31.67
2,778	3/4	6.23	37.90
3,166	3/4	5.08	42.98
3,522	1/2	3.10	46.08
3,696	1/2	1.52	47.60

RECEIVED
AUG 29 1967

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Certification of personal knowledge of Deviation Record:

I hereby certify that I have personal knowledge of the data and facts placed on this form, and that such information is true and complete.



Signature
VERNA DRILLING COMPANY
Company